



Butyric Acid – CAS # 107-92-6

Butyric Acid is a colorless liquid with a putrid odor. It is soluble in water and most common organic solvents. Butyric Acid is stable under recommended storage conditions. Butyric Acid will burn when heated or exposed to an ignition source.

Butyric Acid is available from OXEA in the following packages:

- UN 1H1/Y1.9/150 55-Gallon High Density Polyethylene Drums

- DOT MC 307 or DOT 407 Tank Trucks
- DOT 111A60ALW1 Tank Cars or 111A100W6
- IMO 2 ISO Tank
- Ship Tank and Barge

Storage

Recommended Blanketing	Air ^{1,2}
Recommended Temperature	Ambient
Recommended Pressure	Atmospheric
Bulk Quantities	Outside, detached tanks
Small Containers	Cool, dry, well ventilated area

Handling

- Thoroughly review Material Safety Data Sheet before handling product.
- Keep containers closed when not in use.
- Open containers slowly to allow any excess pressure to vent.
- Keep away from heat, sparks, flame, or other sources of ignition.
- Protect small containers from physical damage.
- Use proper electrical grounding and bonding procedures when loading, unloading, and transferring.¹
- Refer to the OXEA Material Safety Data Sheet for more information on materials to avoid.
- Use spark-resistant tools.
- Electrical equipment and circuits in all storage and handling areas must conform to requirements of national electrical code (Articles 500 and 501) for hazardous location.

See the National Fire Protection Agency (NFPA) #30 “Flammable and Combustible Liquids Code” and consult with qualified fire protection specialists to determine specific storage tank design requirements. Refer to the OXEA Material Safety Data Sheet for more specific health and environmental

information and refer to the OXEA Product Descriptions for additional physical properties and general product information. Material Safety Data Sheet and Product Descriptions for Butyric Acid are available through your OXEA sales representative.

1. Refer to NFPA #77 “Static Electricity” for proper electrical grounding procedures.
2. See the National Fire Protection Agency (NFPA) #30 “Flammable and Combustible Liquids Code” and consult with qualified fire protection specialists to determine specific storage tank design requirements. Domestic Shipping Information

PRODUCT HANDLING GUIDE

2 of 2

Butyric Acid

Materials of Construction for Storage and Transportation

Item	Recommended	Acceptable
Tank	Stainless Steel ¹	-
Piping	Stainless Steel ¹	-
Valves	Stainless Steel ¹	-
Pumps	Stainless Steel ¹	-
Relief Valves	Stainless Steel ¹	-
Gaskets	Glass Filled PTFE ⁴	PTFE ⁴
Pump Seals ²	Single mechanical seal: Stainless steel/Hastelloy C-276 metallic components ³ , Kalrez O- rings	-
Valve Packing	PTFE ⁴	Graphite
Pipe End Connections	Welded and flanged system	-
Heat Exchanger	Product Side: Stainless Steel ¹	-
Hoses	Stainless Steel ¹	-
Tank Truck	Stainless Steel ¹	Aluminum ⁵
Tank Car	Stainless Steel ¹	Aluminum ⁵
ISO Tank	Stainless Steel ¹	-
Barge	Stainless Steel ¹	-
Ship Tank	Stainless Steel ¹	-

1. Type 304 or 316 Stainless Steel.
2. May need to consider double or tandem seal arrangement for odor control.
3. Use Alloy-C-276 seal components for long service life.
4. Polytetrafluoroethylene.
5. Use 3000, 5000, 6000 series Aluminum when the temperature does not exceed 120°F (49°C).

This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should therefore not be construed as guaranteeing specific properties of the products described or their suitability for a particular application. Any existing industrial property rights must be observed. The quality of our products is guaranteed under our General Conditions of Sale.

PH-003-10 03/07

OXEA Corporation
1505 West LBJ Freeway, Suite 400
Dallas, TX 75234
Phone: +1 972-481-2700
P.O. Box 810349
Dallas, TX 75381-0349

OXEA GmbH
Otto-Roelen-Str. 3
46147 Oberhausen
Deutschland/Germany
Tel.: ++49 (0) 208-693-3100