

Sales Specification

Di-n-butylamine

CAS-No. 111-92-2

Sales-
Specifications

Property	Limit	Unit	Test Method	PQR
Di-n-butylamine	min. 99.5	% (w/w)	Gas Chromatography	x
Isobutyl-n-butylamine	max. 0.30	% (w/w)	Gas Chromatography	x
n-Butylamine	max. 0.10	% (w/w)	Gas Chromatography	x
Tri-n-butylamine	max. 0.10	% (w/w)	Gas Chromatography	x
n-Butanol	max. 0.10	% (w/w)	Gas Chromatography	x
Water (Europe) (North America)	max. 0.10	% (w/w)	DIN 51 777 / ASTM D 1364	x
	max. 0.1	% (w/w)	(mod. Karl-Fischer-Method)	
Platinum/Cobalt Color (Hazen/APHA Color)	max. 15		DIN EN 1557 / DIN ISO 6271 / ASTM D 1209	x

Product-No. 50000939

Date of Issue 2010-07-01

Version-No. 1

Additional product number(s) in use for other packaging

OXEA GmbH
Otto-Roelen-Straße 3
46147 Oberhausen
Germany

OXEA Corporation
1505 West LBJ Freeway
Suite 400
Dallas, TX 75234
USA

email: psq@oxea-chemicals.com

Page 1 of 1
10220_SLS_EN_V1a

The parameters marked with x are listed on the Product Quality Report (PQR).
Test methods used are available upon request. Contact your Sales Support for copies.

Typical properties are not part of the sales specification.

This information is based on our present state of knowledge and shall be intended to provide general notes on our products and their field of application. It shall therefore not be construed as guaranteeing specific characteristics of the products described and/or their suitability for a particular application. Any existing industrial property rights shall be observed. The quality of our products is warranted under our General Conditions of Sale.