

OXEA PRODUCT HANDLING GUIDE



1 of 2

n-Undecanal – CAS # 112-44-7

n-Undecanal is a clear, colorless, mobile, oily liquid with an intense, fruity odor. n-Undecanal is a reactive liquid and rapid, uncontrolled polymerization may occur. Exposure to elevated temperatures, oxygen, or contaminants may cause hazardous polymerization.

n-Undecanal can spontaneously combust if wiped up with rags, paper towels, etc.

n-Undecanal is available from OXEA in the following packages:

- UN 1A1/X1.2/300 55-Gallon Carbon Steel Drums with Morton 105 R4 Lining or equivalent
- MC 307 or DOT 407 Tank Trucks
- IMO 1 ISO Tanks

Storage

Recommended Blanketing	Nitrogen ^{1,2,3}
Recommended Temperature	
Maximum	120°F (48.9°C)
Minimum	32°F (0°C)
Recommended Pressure	Atmospheric
Bulk Quantities	Outside, detached tanks
Small Containers	Cool, dry, well ventilated areas

Handling

- Thoroughly review Material Safety Data Sheet before handling product.
- Keep containers closed and Nitrogen padded when not in use.
- Open containers slowly to allow any excess pressure to vent.
- Keep away from heat, sparks, flame, or other sources of ignition.
- Protect small containers from physical damage.
- Use proper electrical grounding and bonding procedures when loading, unloading, and transferring.¹
- Refer to the OXEA Material Safety Data Sheet for more information on materials to avoid.
- Use spark-resistant tools.
- Electrical equipment and circuits in all storage and handling areas must conform to requirements of national electrical code (Articles 500 and 501) for hazardous location.
- Spontaneous Combustion may occur in rags or paper towels if used for spill clean-up.

See the National Fire Protection Agency (NFPA) #30 “Flammable and Combustible Liquids Code” and consult with qualified fire protection specialists to determine specific storage tank design requirements. Refer to the OXEA Material Safety Data Sheet for more specific health and environmental

information and refer to the OXEA Product Descriptions for additional physical properties and general product information. Material Safety Data Sheet and Product Descriptions for n-Undecanal are available through your OXEA sales representative.

1. Refer to NFPA #77 “Static Electricity” for proper electrical grounding procedures.
2. See the National Fire Protection Agency (NFPA) #30 “Flammable and Combustible Liquids Code” and consult with qualified fire protection specialists to determine specific storage tank design requirements.
3. Blanketing should be used to retain quality in long-term storage conditions.

PRODUCT HANDLING GUIDE

2 of 2

n-Undecanal

Materials of Construction for Storage and Transportation

Item	Recommended	Acceptable
Tank	Stainless Steel ¹	Lined Carbon Steel ² , Aluminum
Piping	Stainless Steel ¹	Carbon Steel ⁴ , Aluminum
Valves	Stainless Steel ¹	Cast Iron, Carbon Steel ⁴
Pumps	Stainless Steel ¹	Cast Iron, Carbon Steel ⁴
Relief Valves	Stainless Steel ¹	Cast Iron, Carbon Steel ⁴
Gaskets	Glass Filled PTFE ^{3,5}	EPDM ⁶
Pump Seals	Mechanical Seal: Double mechanical seal, back to back arrangement carbon to silicon carbide faces, Kalrez O-rings	Mechanical Seal: carbon to tungsten carbide faces, EPDM ⁶ O-rings
Valve Packing	PTFE ⁵	Graphite
Pipe End Connections	Welded and flanged system	Threaded with PTFE ⁵ tape thread lubricant
Heat Exchanger	Product Side: Stainless Steel ¹	-
Hoses	Stainless Steel ¹	EPDM ⁶ , Silicone
Tank Truck	Stainless Steel ¹	-
Tank Car	Lined Carbon Steel ²	Stainless Steel ¹
Barge	Stainless Steel ¹	-
Ship Tank	Stainless Steel ¹	-

1. Type 304 or 316 Stainless Steel.
2. Lining refers to a high baked phenolic.
3. May be use if an increase in iron content, color, or the presence of high boiling point impurities is not a problem.
4. Maximum storage temperature 120°F (49°C).
5. Polytetrafluoroethylene.
6. Ethylene – Propylene – diene – monomer – (peroxide cured grade).

This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should therefore not be construed as guaranteeing specific properties of the products described or their suitability for a particular application. Any existing industrial property rights must be observed. The quality of our products is guaranteed under our General Conditions of Sale.

OXEA Corporation
1505 West LBJ Freeway, Suite 400
Dallas, TX 75234
Phone: +1 972-481-2700
P.O. Box 810349
Dallas, TX 75381-0349

OXEA GmbH
Otto-Roelen-Str. 3
46147 Oberhausen
Deutschland/Germany
Tel.: ++49 (0) 208-693-3100

PRODUCT HANDLING GUIDE

3 of 3

This information is based on our present state of knowledge and is intended to provide general notes on our products and their uses. It should therefore not be construed as guaranteeing specific properties of the products described or their suitability for a particular application. Any existing industrial property rights must be observed. The quality of our products is guaranteed under our General Conditions of Sale.

PH-208-10 03/07

OXEA Corporation
1505 West LBJ Freeway, Suite 400
Dallas, TX 75234
Phone: +1 972-481-2700
P.O. Box 810349
Dallas, TX 75381-0349

OXEA GmbH
Otto-Roelen-Str. 3
46147 Oberhausen
Deutschland/Germany
Tel.: ++49 (0) 208-693-3100