

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision  
Supersedes Version

3 .00\*\*\*  
2 .01\*\*\*

Revision Date  
Issuing date

14-Oct-2016  
14-Oct-2016

## SECTION 1: Identification of the substance / mixture and of the company / undertaking

### 1.1. Product identifier

Identification of the  
substance/preparation

**n-Butanol**

Chemical Name Butan-1-ol\*\*\*  
CAS-No 71-36-3  
EC No. 200-751-6  
Registration number (REACH) 01-2119484630-38\*\*\*

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Intermediate  
Formulation  
Distribution of substance  
coatings  
cleaning agent  
Lubricants and lubricant additives  
Metal working fluids / rolling oils  
laboratory chemicals  
Polymer processing  
consumer care product\*\*\*

Uses advised against

None

### 1.3. Details of the supplier of the safety data sheet

Company/Undertaking  
Identification

**OXEA GmbH**  
Otto-Roelen-Str. 3  
D-46147 Oberhausen  
Germany

Product Information

Product Stewardship  
FAX: +49 (0)208 693 2053  
email: psq@oxea-chemicals.com

### 1.4. Emergency telephone number

Emergency telephone number +44 (0) 1235 239 670 (UK)  
available 24/7\*\*\*

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

This substance is classified based on Directive 1272/2008/EC and its amendments (CLP Regulation)

Flammable liquid Category 3, H226\*\*\*  
Acute oral toxicity Category 4, H302\*\*\*  
Skin corrosion/irritation Category 2, H315\*\*\*

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

Serious eye damage/eye irritation Category 1, H318\*\*\*  
Target Organ Systemic Toxicant - Single exposure Category 3, H335, Category 3, H336\*\*\*

## Additional information

For full text of Hazard- and EU Hazard-statements see SECTION 16.\*\*\*

## 2.2. Label elements

Labelling according to Regulation 1272/2008/EC and its amendments (CLP Regulation).\*\*\*

### Hazard pictograms



### Signal word

**Danger**

### Hazard statements

H226: Flammable liquid and vapour.  
H302: Harmful if swallowed.  
H335: May cause respiratory irritation.  
H315: Causes skin irritation.  
H318: Causes serious eye damage.  
H336: May cause drowsiness or dizziness.

### Precautionary statements

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261: Avoid breathing gas/mist/vapours.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310: Immediately call a POISON CENTER/doctor.  
P403 + P235: Store in a well ventilated place. Keep cool.\*\*\*

## 2.3. Other hazards

Vapour is heavier than air and can travel considerable distance to a source of ignition and flashback  
Vapours may form explosive mixture with air  
Components of the product may be absorbed into the body by inhalation, ingestion and through the skin

### PBT and vPvB assessment

This substance is not considered to be persistent, bioaccumulating nor toxic (PBT), nor very persistent nor very bioaccumulating (vPvB)\*\*\*

## SECTION 3: Composition / information on ingredients

### 3.1. Substances

\*\*\*

Component	CAS-No	REACH-No	1272/2008/EC	Concentration (%)
-----------	--------	----------	--------------	-------------------

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

Butan-1-ol	71-36-3	01-2119484630-38** *	Flam. Liq. 3; H226 Acute Tox. 4; H302 STOT SE 3; H335 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336***	> 99,80
------------	---------	-------------------------	--	---------

For full text of Hazard- and EU Hazard-statements see SECTION 16.\*\*\*

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Keep at rest. Aerate with fresh air. When symptoms persist or in all cases of doubt seek medical advice.

#### Skin

Wash off immediately with soap and plenty of water. When symptoms persist or in all cases of doubt seek medical advice.

#### Eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. Immediate medical attention is required.

#### Ingestion

Rinse mouth. Call a physician immediately. If conscious, drink plenty of water. Do not induce vomiting without medical advice.

### 4.2. Most important symptoms and effects, both acute and delayed

#### Main symptoms

cough, headache, dizziness, drowsiness, nausea, vomiting, abdominal pain, unconsciousness, diarrhea.

#### Special hazard

Lung irritation, Pneumonia.

### 4.3. Indication of any immediate medical attention and special treatment needed

#### General advice

Remove contaminated, soaked clothing immediately and dispose of safely. If unconscious place in recovery position and seek medical advice. First aider needs to protect himself.

Treat symptomatically. If ingested, irrigate the stomach using activated charcoal. Chemical pneumonitis could follow respiratory exposure.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

dry chemical, carbon dioxide (CO<sub>2</sub>), water spray, alcohol-resistant foam

#### Unsuitable Extinguishing Media

Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

Under conditions giving incomplete combustion, hazardous gases produced may consist of:  
carbon monoxide (CO)  
carbon dioxide (CO<sub>2</sub>)  
Combustion gases of organic materials must in principle be graded as inhalation poisons  
Vapour is heavier than air and can travel considerable distance to a source of ignition and flashback  
Vapours may form explosive mixture with air

## 5.3. Advice for firefighters

### Special protective equipment for firefighters

Fire fighter protection should include a self-contained breathing apparatus (NIOSH-approved or EN 133) and full fire-fighting turn out gear.

### Precautions for firefighting

Cool containers / tanks with water spray. Dike and collect water used to fight fire. Keep people away from and upwind of fire. Do not allow run-off from fire fighting to enter drains or water courses. Foam should be applied in large quantities as it is broken down to some extent by the product.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: For personal protective equipment see section 8. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep people away from and upwind of spill/leak. Ensure adequate ventilation, especially in confined areas. Keep away from heat and sources of ignition.  
For emergency responders: Personal protection see section 8.\*\*\*

### 6.2. Environmental precautions

Prevent further leakage or spillage. Do not discharge product into the aquatic environment without pretreatment (biological treatment plant).

### 6.3. Methods and material for containment and cleaning up

#### Methods for containment

Stop the flow of material, if possible without risk. Dike spilled material, where this is possible.

#### Methods for cleaning up

Soak up with inert absorbent material (e.g. universal binder). Keep in suitable, closed containers for disposal. If liquid has been spilt in large quantities clean up promptly by scoop or vacuum. Dispose of in accordance with local regulations. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).

### 6.4. Reference to other sections

For personal protective equipment see section 8.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Further info may be available in the appropriate Exposure scenarios in the annex to this SDS.\*\*\*

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

## **Advice on safe handling**

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Provide sufficient air exchange and/or exhaust in work rooms.

## **Hygiene measures**

When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product.

## **Advice on the protection of the environment**

See Section 8: Environmental exposure controls.

## **Incompatible products**

strong oxidizing agents  
acids  
acid chlorides  
reducing agents

## **7.2. Conditions for safe storage, including any incompatibilities**

### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). In case of fire, emergency cooling with water spray should be available. Ground and bond containers when transferring material. Vapour is heavier than air and can travel considerable distance to a source of ignition and flashback. Vapours may form explosive mixture with air.

### **Technical measures/Storage conditions**

Keep containers tightly closed in a cool, well-ventilated place. Handle and open container with care.

### **Suitable material**

stainless steel, mild steel

### **Unsuitable material**

Attacks some forms of plastic and rubber, Natural Rubber

### **Temperature class**

T2

## **7.3. Specific end use(s)**

Intermediate  
Formulation  
Distribution of substance  
coatings  
cleaning agent  
Lubricants and lubricant additives  
Metal working fluids / rolling oils  
laboratory chemicals  
Polymer processing  
consumer care product\*\*\*  
For specific end use information see the annex of this safety data sheet\*\*\*

## **SECTION 8: Exposure controls / personal protection**

### **8.1. Control parameters**

#### **Exposure limits European Union**

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

No exposure limits established.

## Exposure limits UK

### **EH40 WELs**

Component	TWA (mg/m <sup>3</sup> )	TWA (ppm)	STEL (mg/m <sup>3</sup> )	STEL (ppm)
Butan-1-ol CAS: 71-36-3			154***	50***

### **EH40 WELs and Appendix 5 Carcinogens**

Component	Skin Absorption	Asphyxia	Respiratory irritant	included w/o limits	Carcinogen
Butan-1-ol CAS: 71-36-3	Yes***				

#### **Note**

For details and further information please refer to the original regulation.

## DNEL & PNEC

### **Butan-1-ol, CAS: 71-36-3**

#### Workers

DN(M)EL - long-term exposure - local effects - Inhalation

\*\*\*

310 mg/m<sup>3</sup>

#### General population

\*\*\*

DN(M)EL - long-term exposure - local effects - Inhalation

55 mg/m<sup>3</sup>

DN(M)EL - long-term exposure - systemic effects - Oral

3,125 mg/kg bw/day

#### Environment

\*\*\*

PNEC aqua - freshwater

0,082 mg/l

PNEC aqua - marine water

0,0082 mg/l

PNEC aqua - intermittent releases

2,25 mg/l

PNEC STP

2476 mg/l

PNEC sediment - freshwater

0,178 mg/kg

PNEC sediment - marine water

0,0178 mg/kg

PNEC soil

0,015 mg/kg

## **8.2. Exposure controls**

### **Special adaptations (REACH)**

Not applicable.\*\*\*

### **Appropriate Engineering controls**

General or dilution ventilation is frequently insufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Explosion-proof equipment (for example fans, switches, and grounded ducts) should be used in mechanical ventilation systems.

### **Personal protective equipment**

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## General industrial hygiene practice

Avoid contact with skin, eyes and clothing. Do not breathe vapours or spray mist. Ensure that eyewash stations and safety showers are close to the workstation location.

## Hygiene measures

When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product.

## Eye protection

Tightly fitting safety goggles. In addition to goggles, wear a face shield if there is a reasonable chance for splash to the face.

Equipment should conform to EN 166

## Hand protection

Wear protective gloves. Recommendations are listed below. Other protective material may be used, depending on the situation, if adequate degradation and permeation data is available. If other chemicals are used in conjunction with this chemical, material selection should be based on protection for all chemicals present.

<b>Suitable material</b>	butyl-rubber
<b>Evaluation</b>	according to EN 374: level 6
<b>Glove thickness</b>	approx 0,3 mm
<b>Break through time</b>	> 480 min

<b>Suitable material</b>	nitrile rubber
<b>Evaluation</b>	according to EN 374: level 6
<b>Glove thickness</b>	approx 0,55 mm
<b>Break through time</b>	> 480 min

## Skin and body protection

Impervious clothing. Wear face-shield and protective suit for abnormal processing problems.

## Respiratory protection

Respirator with A filter. Full mask with above mentioned filter according to producers using requirements or self-contained breathing apparatus. Equipment should conform to EN 136 or EN 140 and EN 143.

## Environmental exposure controls

If possible use in closed systems. If leakage can not be prevented, the substance needs to be suck off at the emersion point, if possible without danger. Observe the exposure limits, clean exhaust air if needed. If recycling is not practicable, dispose of in compliance with local regulations. Inform the responsible authorities in case of leakage into the atmosphere, or of entry into waterways, soil or drains.

## Additional advice

Further details on substance data can be found in the registration dossier under the following link:  
<http://echa.europa.eu/information-on-chemicals/registered-substances>. For specific exposure controls see the annex to this safety data sheet.\*\*\*

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	liquid
<b>Colour</b>	colourless
<b>Odour</b>	alcoholic
<b>Odour threshold</b>	No data available
<b>pH</b>	neutral
<b>Melting point/range</b>	< -90 °C @ 1013 hPa (Pour point)***

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

**Boiling point/range** 119 °C @ 1013 hPa  
**Flash point** 35 °C @ 1013 hPa\*\*\*  
**Method** ISO 2719  
**Evaporation rate** No data available  
**Flammability (solid, gas)** Does not apply, the substance is a liquid  
**Lower explosion limit** 1,4 Vol %  
**Upper explosion limit** 11,3 Vol %

**Vapour pressure** \*\*\*  
Values [hPa] Values [kPa] Values [atm] @ °C @ °F Method  
10 1 0,010 20 68  
53 5,3 0,052 50 122  
**Vapour density** 2,6 (Air = 1) @ 20 °C (68 °F)

**Relative density** \*\*\*  
Values @ °C @ °F Method  
0,81 20 68 DIN 51757

**Solubility** 66 g/l @ 20 °C, in water, OECD 105\*\*\*  
**log Pow** 1 (measured), OECD 117  
**Autoignition temperature** 355 °C @ 1013 hPa\*\*\*  
**Method** DIN 51794  
**Decomposition temperature** No data available  
**Viscosity** 2,947 mPa\*s @ 20 °C  
**Method** dynamic, DIN 51562  
**Explosive properties** Does not apply, substance is not explosive. There are no chemical groups associated with explosive properties  
**Oxidizing properties** Does not apply, substance is not oxidising. There are no chemical groups associated with oxidizing properties

## 9.2. Other information

**Molecular weight** 74,12  
**Molecular formula** C<sub>4</sub> H<sub>10</sub> O  
**Refractive index** 1,399 @ 20 °C  
**Surface tension** 69,9 mN/m (1 g/l @ 20°C), OECD 115

## SECTION 10: Stability and Reactivity

### 10.1. Reactivity

The reactivity of the product corresponds to the typical reactivity shown by the substance group as described in any text book on organic chemistry.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air.

### 10.4. Conditions to avoid

Avoid contact with heat, sparks, open flame and static discharge. Avoid any source of ignition.



# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## 10.5. Incompatible materials

strong oxidizing agents, acids, acid chlorides, reducing agents.

## 10.6. Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Likely routes of exposure Ingestion, Inhalation, Eye contact, Skin contact\*\*\*

Acute toxicity				
Butan-1-ol (71-36-3)				
Routes of Exposure	Endpoint	Values	Species	Method
Oral	LD50	2292 mg/kg	rat, female	OECD 401
Inhalative	LC0	> 17,76 mg/l (4h)	rat, male/female	OECD 403
Dermal	LD50	3430 mg/kg	rabbit male***	OECD 402

#### Butan-1-ol, CAS: 71-36-3

##### Assessment

Based on available data, the classification criteria are not met for:

Acute oral toxicity

Acute dermal toxicity

Acute inhalation toxicity\*\*\*

Irritation and corrosion				
Butan-1-ol (71-36-3)				
Target Organ Effects	Species	Result	Method	
Skin	rabbit	irritating	Draize Test	
Eyes	rabbit	severe irritation	OECD 405	

#### Butan-1-ol, CAS: 71-36-3

##### Assessment

The available data lead to the classification given in section 2\*\*\*

Sensitization				
Butan-1-ol (71-36-3)				
Target Organ Effects	Species	Evaluation	Method	
Skin	guinea pig	not sensitizing	OECD 406	read across
Skin***		not sensitizing***	QSAR***	read across***

#### Butan-1-ol, CAS: 71-36-3

##### Assessment

Based on available data, the classification criteria are not met for:

Skin sensitization

For respiratory sensitization, no data are available\*\*\*

Subacute, subchronic and prolonged toxicity				
Butan-1-ol (71-36-3)				
Type	Dose	Species	Method	

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

Version / Revision 3 .00\*\*\*

Subchronic toxicity	NOAEL: 125 mg/l/d (90d)***	rat, male/female		Oral
Subchronic toxicity	LOAEL: 500 mg/kg/d (90d)***	rat, male/female		Oral
Subchronic toxicity	NOAEL: ~ 2,35 mg/l/d (90d)	rat, male/female	EPA OTS 798.2450	Inhalation

## **Butan-1-ol, CAS: 71-36-3**

### **Assessment**

Based on available data, the classification criteria are not met for:  
STOT RE\*\*\*

<b>Carcinogenicity, Mutagenicity, Reproductive toxicity</b>					
<b>Butan-1-ol (71-36-3)</b>					
Type	Dose	Species	Evaluation	Method	
Mutagenicity		V79 cells, Chinese hamster	negative	OECD 476 (Mammalian Gene Mutation) HPRT***	In vitro study***
Mutagenicity		V79 cells, Chinese hamster***	negative	Chromosomal Aberration	In vitro study***
Mutagenicity		Salmonella typhimurium	negative	Ames test	
Mutagenicity		mouse	negative	OECD 474	Oral in vivo micronucleus test***
Reproductive toxicity	NOAEL 18,5 mg/l	rat, parental			Inhalation
Reproductive toxicity	NOAEL 18,5 mg/l	rat, 1. Generation, male/female			Inhalation
Mutagenicity	NOAEL 5000 mg/kg/d	rat, parental, female***		Oral	
Developmental Toxicity	NOAEL 1454 mg/kg/d	rat		Oral	Maternal toxicity, Fetal toxicity
Developmental Toxicity	NOAEL 5654 mg/kg/d	rat		Oral	Teratogenicity
Developmental Toxicity	NOAEL 10,8 mg/l	rat		Inhalation	Maternal toxicity, Fetal toxicity
Developmental Toxicity	NOAEL 24,7 mg/l	rat		Inhalation	Teratogenicity
Carcinogenicity***	No data available***				
Reproductive toxicity***	NOAEL 500 mg/kg/d***	rat, male/female***		Oral***	
Reproductive toxicity***	NOAEC: 2000 ppm***	rat, male/female***		OECD 416 Inhalation***	read across***

## **Butan-1-ol, CAS: 71-36-3**

### **CMR Classification**

The available data on CMR properties are summarized in the table above. They do not indicate a classification into categories 1A or 1B\*\*\*

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Evaluation

In vitro tests did not show mutagenic effects  
Did not show mutagenic effects in animal experiments  
In the absence of specific alerts no cancer testing is required\*\*\*

## Butan-1-ol, CAS: 71-36-3

### Main symptoms

cough, headache, dizziness, drowsiness, nausea, vomiting, abdominal pain, unconsciousness, diarrhoea.

### Target Organ Systemic Toxicant - Single exposure

The available data lead to the classification given in section 2\*\*\*

### Target Organ Systemic Toxicant - Repeated exposure

Based on available data, the classification criteria are not met for:  
STOT RE\*\*\*

### Aspiration toxicity

Based on the viscosity a potential aspiration hazard cannot be excluded

### Other adverse effects

Components of the product may be absorbed into the body by inhalation, ingestion and through the skin.

### Note

Handle in accordance with good industrial hygiene and safety practice. Further details on substance data can be found in the registration dossier under the following link:

<http://echa.europa.eu/information-on-chemicals/registered-substances>.\*\*\*

## SECTION 12: Ecological information

### 12.1. Toxicity

Acute aquatic toxicity			
Butan-1-ol (71-36-3)			
Species	Exposure time	Dose	Method
Pimephales promelas (fathead minnow)	96h	LC50: 1376 mg/l	OECD 203
Daphnia magna (Water flea)	48h	EC50: 1328 mg/l	OECD 202
Pseudokirchneriella subcapitata	96h	EC50: 225 mg/l (Growth rate)	OECD 201

Long term toxicity				
Butan-1-ol (71-36-3)				
Type	Species	Dose	Method	
Reproductive toxicity	Daphnia magna (Water flea)	NOEC: 4,1 mg/l (21d)	OECD 211	
Reproductive toxicity	Daphnia magna (Water flea)	EC50: 18 mg/l/21d	OECD 211	
Aquatic toxicity***	Pseudokirchneriella subcapitata***	EC10: 134 mg/l (96 h)***	OECD 201 Growth rate***	

### 12.2. Persistence and degradability

## Butan-1-ol, CAS: 71-36-3

### Biodegradation

92 % (15 d), Sewage, aerobic, domestic, non-adapted, BOD.

### Abiotic Degradation

Butan-1-ol (71-36-3)		
Type	Result	Method

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

Hydrolysis***	No data available***	
Photolysis***	No data available***	

## 12.3. Bioaccumulative potential

Butan-1-ol (71-36-3)		
Type	Result	Method
log Pow***	1 @ 25 °C***	OECD 117***
BCF***	No data available***	

## 12.4. Mobility in soil

Butan-1-ol (71-36-3)		
Type	Result	Method
Surface tension***	69,9 mN/m (1 g/l @ 20°C)***	OECD 115***
Adsorption/Desorption***	log Koc: 0,388***	calculated***
Distribution to environmental compartments***	Air: 27,07 Soil: 0,04 Water: 72,85 Sediment: 0,04 Suspended sediment: 0 Biota: 0***	calculated***

## 12.5. Results of PBT and vPvB assessment

### Butan-1-ol, CAS: 71-36-3 PBT and vPvB assessment

This substance is not considered to be persistent, bioaccumulating nor toxic (PBT), nor very persistent nor very bioaccumulating (vPvB)

## 12.6. Other adverse effects

### Butan-1-ol, CAS: 71-36-3 No data available\*\*\*

#### Note

Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Product Information

Disposal required in compliance with all waste management related state and local regulations. The choice of the appropriate method of disposal depends on the product composition by the time of disposal as well as the local statutes and possibilities for disposal.

Hazardous waste according to European Waste Catalogue (EWC)

#### Uncleaned empty packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

## SECTION 14: Transport information

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## ADR/RID

14.1. UN number \*\*\* UN 1120  
14.2. UN proper shipping name \*\*\* Butanols  
14.3. Transport hazard class(es) \*\*\* 3  
14.4. Packing group \*\*\* III  
14.5. Environmental hazards no\*\*\*  
14.6. Special precautions for user \*\*\*  
ADR Tunnel restriction code (D/E)  
Classification Code F1  
Hazard Number 30

## ADN

ADN: Container and Tanker  
14.1. UN number \*\*\* UN 1120  
14.2. UN proper shipping name \*\*\* Butanols  
14.3. Transport hazard class(es) \*\*\* 3  
14.4. Packing group \*\*\* III  
14.5. Environmental hazards no\*\*\*  
14.6. Special precautions for user \*\*\*  
Classification Code F1  
Hazard Number 30

## ICAO-TI / IATA-DGR

14.1. UN number \*\*\* UN 1120  
14.2. UN proper shipping name \*\*\* Butanols\*\*\*  
14.3. Transport hazard class(es) \*\*\* 3  
14.4. Packing group \*\*\* III  
14.5. Environmental hazards no\*\*\*  
14.6. Special precautions for user no data available\*\*\*

## IMDG

14.1. UN number \*\*\* UN 1120  
14.2. UN proper shipping name \*\*\* Butanols\*\*\*  
14.3. Transport hazard class(es) \*\*\* 3  
14.4. Packing group \*\*\* III  
14.5. Environmental hazards no\*\*\*  
14.6. Special precautions for user \*\*\*  
EmS F-E, S-D  
14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code \*\*\*  
Product name n-Butyl alcohol  
Ship type 3\*\*\*  
Pollution category Z

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Regulation 1272/2008, Annex VI

##### Butan-1-ol, CAS: 71-36-3

<b>Classification</b>	Flam. Liq. 3; H226 Acute Tox. 4*; H302 STOT SE 3; H335 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336
<b>Hazard pictograms</b>	GHS02 Flame GHS05 Corrosion GHS07 Exclamation mark***
<b>Signal word</b>	Danger
<b>Hazard statements</b>	H226, H302, H335, H315, H318, H336

##### DI 2012/18/EU (Seveso III) \*\*\*

<b>Category</b>	Annex I, part 1: P5a - c; depending on conditions***
-----------------	---

##### DI 1999/13/EC (VOC Guideline)

\*\*\*

Component	Status
Butan-1-ol CAS: 71-36-3	regulated***

#### International Inventories

##### **Butan-1-ol, CAS: 71-36-3**

AICS (AU)  
DSL (CA)  
IECSC (CN)  
EC-No. 2007516 (EU)  
ENCS (2)-3049 (JP)  
ISHL (2)-3049 (JP)  
ISHL 2-(8)-299 (JP)  
KECI KE-03867 (KR)  
INSQ (MX)\*\*\*  
PICCS (PH)  
TSCA (US)  
NZIoC (NZ)  
TCSI (TW)\*\*\*

#### National regulatory information Great Britain

This classification following EG guidelines is also in accordance with the Chemicals (Hazard Information and Packaging for Supply) Regulation CHIP (as amended).

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Releases to air (Pollution Inventory Substances)

not subject\*\*\*

## Releases to water (Pollution Inventory Substances)

not subject\*\*\*

## Releases to sewer (Pollution Inventory Substances)

not subject\*\*\*

For details and further information please refer to the original regulation\*\*\*

## 15.2. Chemical safety assessment

The Chemical Safety Report (CSR) has been generated. For Exposure Scenarios see the annex.\*\*\*

## SECTION 16: Other information

### Full text of H-Statements referred to under sections 2 and 3

H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

### Abbreviations

A table of terms and abbreviations can be found under the following link:

[http://echa.europa.eu/documents/10162/13632/information\\_requirements\\_r20\\_en.pdf](http://echa.europa.eu/documents/10162/13632/information_requirements_r20_en.pdf)

### Training advice

For effective first-aid, special training / education is needed.

### Sources of key data used to compile the datasheet

Information contained in this safety data sheet is based on Oxea owned data and public sources deemed valid or acceptable. The absence of data elements required by OSHA, ANSI or Annex II, Regulation 1907/2006/EC indicates, that no data meeting these requirements is available.

### Further information for the safety data sheet

Changes against the previous version are marked by \*\*\*. Observe national and local legal requirements. For more information, other material safety data sheets or technical data sheets please consult the Oxea homepage ([www.oxea-chemicals.com](http://www.oxea-chemicals.com)).

### Disclaimer

**For industrial use only.** The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. Oxea makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards.

**End of Safety Data Sheet**

## Annex to the extended Safety Data Sheet (eSDS)

### General information

Acute Health Hazard:

Qualitative approach used to conclude safe use.

For consumer applications in the following usage areas please contact Oxea (psq@oxea-chemicals.com):

Uses in coatings

Use in Cleaning Agents

lubricants

Consumer uses e.g. as a carrier in cosmetics/personal care products, perfumes and fragrances. Note: For cosmetic and personal care products, risk assessment only required for the environment under REACH as human health is covered by alternative legislation

For specific information regarding the SPERC used please refer to the ESIG webpage  
[www.esig.org/en/regulatory-information/reach/ges-library](http://www.esig.org/en/regulatory-information/reach/ges-library)

Other combinations of operational conditions may also be safe. Please contact Oxea in case your local operational conditions differ from the ones described below and you are unsure if they are also safe

### Operational conditions and risk management measures

Wear protective gloves and eye/face protection. Minimization of manual phases. Avoid direct contact with the chemical/the product/the preparation by establishing organisational measures. Supervision in place to check that the RMMs in place are being used correctly and OCs followed.

### Exposure scenario identification

- |      |  |
|------|--|
| 1    | <b>Industrial use resulting in manufacture of another substance (use of intermediates)</b> |
| 2    | <b>Formulation &amp; (re)packing of substances and mixtures</b>                            |
| 3    | <b>Distribution of substance</b>   |
| 4    | <b>Uses in coatings</b>  |
| 5*** | <b>Uses in coatings***</b>   |
| 6    | <b>Use in Cleaning Products</b>  |
| 7    | <b>Use in Cleaning Products</b>  |
| 8    | <b>lubricants</b>  |
| 9    | <b>lubricants</b>  |
| 10   | <b>Metal working fluids / rolling oils</b>   |
| 11   | <b>Metal working fluids / rolling oils</b>   |
| 12   | <b>Use in laboratories</b>   |
| 13   | <b>Polymer processing</b>  |

### Number of the ES 1

Short title of the exposure scenario

**Industrial use resulting in manufacture of another substance (use of intermediates)**

List of use descriptors



# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

## Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites  
SU8: Manufacture of bulk, large scale chemicals (including petroleum products)  
SU9: Manufacture of fine chemicals

## Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure  
PROC2: Use in closed, continuous process with occasional controlled exposure  
PROC3: Use in closed batch process (synthesis or formulation)  
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises  
PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities  
PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities  
PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

## Environmental release categories [ERC]

ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates)

## Product characteristics

Refer to attached safety data sheets

## Processes and activities covered by the exposure scenario

Manufacture of the substance or use as an intermediate, process chemical or extracting agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

## Further explanations

Industrial use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Assumes a good basic standard of occupational hygiene is implemented

## Contributing Scenarios

<b>Number of the contributing scenario</b>	<b>1</b>
<b>Contributing exposure scenario controlling environmental exposure for ERC 6a</b>	

### Further specification

assessment tool used: Chesar 2.3\*\*\*

#### Amounts used

Daily amount per site: 735 to

Annual amount per site: 242705 to

#### Environment factors not influenced by risk management

River flow rate: 18000 m<sup>3</sup>/d

Local freshwater dilution factor: 10

Local marine water dilution factor: 100

#### Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 0.005 %

Release fraction to wastewater from process: 0.0002 %

Release fraction to soil from process: 0.1%

#### Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Onsite treatment off-air. Upgrade Systems in place or implement additional treatment. Assumed Efficiency: 99.9 % Onsite

treatment wastewater. Apply acclimated biological treatment. Assumed Efficiency: 99.99 %\*\*\*

#### Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m<sup>3</sup>/d): 2000

The minimum grade of elimination in the sewage plant is (%): 87.4

Do not apply industrial sludge to natural soils\*\*\*

<b>Number of the contributing scenario</b>	<b>2</b>
--	----------

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Contributing exposure scenario controlling worker exposure for PROC 1

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

Number of the contributing scenario 3

## Contributing exposure scenario controlling worker exposure for PROC 2

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

Number of the contributing scenario 4

## Contributing exposure scenario controlling worker exposure for PROC 3

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

Number of the contributing scenario 5

## Contributing exposure scenario controlling worker exposure for PROC 4

### Further specification

assessment tool used: Chesar 2.3\*\*\*

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

6

## Contributing exposure scenario controlling worker exposure for PROC 8a

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

## Number of the contributing scenario

7

## Contributing exposure scenario controlling worker exposure for PROC 8b

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 95 % (inhalative).\*\*\*

## Number of the contributing scenario

8

## Contributing exposure scenario controlling worker exposure for PROC 9

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

## Exposure estimation and reference to its source

### Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

Fresh Water (Pelagic)	PEC: 0.014 mg/l; RCR: 0.166
Fresh Water (Sediment)	PEC: 0.052 mg/kg dw; RCR: 0.293
Marine Water (Pelagic)	PEC: 0.001 mg/l; RCR: 0.175
Marine Water (Sediment)	PEC: 0.006 mg/kg dw; RCR: 0.310
Agricultural Soil	PEC: 0.0020 mg/kg dw; RCR: 0.104
Sewage Treatment Plant (Effluent)	PEC: 0.092 mg/l; RCR: 0.0000

### Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]. Exposure estimates are given for either short-term or long-term exposure depending on which lead to more conservative risk characterisation ratios.

Proc 1	EE(inhal): 0.031
Proc 2	EE(inhal): 15.44
Proc 3	EE(inhal): 30.88
Proc 4	EE(inhal): 61.77
Proc 8a	EE(inhal): 15.44
Proc 8b	EE(inhal): 3.861
Proc 9	EE(inhal): 15.44

### Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 1	RCR(inhal): 0.0001
Proc 2	RCR(inhal): 0.05
Proc 3	RCR(inhal): 0.10
Proc 4	RCR(inhal): 0.199
Proc 8a	RCR(inhal): 0.05
Proc 8b	RCR(inhal): 0.012
Proc 9	RCR(inhal): 0.05

## Number of the ES 2

Short title of the exposure scenario

## Formulation & (re)packing of substances and mixtures

## List of use descriptors

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

## Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites

SU10: Formulation [mixing] of preparations and/or re-packaging (excluding alloys)

## Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC15: Use as laboratory reagent

## Environmental release categories [ERC]

ERC2: Formulation of preparations (mixtures)

## Product characteristics

Refer to attached safety data sheets

## Processes and activities covered by the exposure scenario

Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.

## Further explanations

Industrial use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Assumes a good basic standard of occupational hygiene is implemented

Assumes an advanced standard of occupational Health and Safety Management System\*\*\*

## Contributing Scenarios

**Number of the contributing scenario**

**1**

**Contributing exposure scenario controlling environmental exposure for ERC 2**

## Further specification

SpERC ESVOC 2.2.v1 (ESVOC 4), release factors for (Sp)ERC were modified, assessment tool used: Chesar 2.3.\*\*\*

## Amounts used

Daily amount per site: 133 to

Annual amount per site: 40000 to

## Environment factors not influenced by risk management

River flow rate: 18000 m<sup>3</sup>/d Local freshwater dilution factor: 10 Local marine water dilution factor: 100

## Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 0.05 %

Release fraction to wastewater from process: 0.0005 %

Release fraction to soil from process: 0.01%

## Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Onsite treatment off-air. Upgrade Systems in place or implement additional treatment. Assumed Efficiency: 95 % Onsite treatment wastewater. Apply acclimated biological treatment. Assumed Efficiency: 99.9 %\*\*\*

## Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m<sup>3</sup>/d): 2000

The minimum grade of elimination in the sewage plant is (%): 87.4

Do not apply industrial sludge to natural soils\*\*\*

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

**Number of the contributing scenario** 2  
**Contributing exposure scenario controlling worker exposure for PROC 1**

**Further specification**

assessment tool used: Chesar 2.3\*\*\*

**Product characteristics**

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

**Number of the contributing scenario** 3  
**Contributing exposure scenario controlling worker exposure for PROC 2**

**Further specification**

assessment tool used: Chesar 2.3\*\*\*

**Product characteristics**

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

**Number of the contributing scenario** 4  
**Contributing exposure scenario controlling worker exposure for PROC 3**

**Further specification**

assessment tool used: Chesar 2.3\*\*\*

**Product characteristics**

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

**Number of the contributing scenario** 5  
**Contributing exposure scenario controlling worker exposure for PROC 4**

**Further specification**

assessment tool used: Chesar 2.3\*\*\*

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

6

## Contributing exposure scenario controlling worker exposure for PROC 5

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

## Number of the contributing scenario

7

## Contributing exposure scenario controlling worker exposure for PROC 8a

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

## Number of the contributing scenario

8

## Contributing exposure scenario controlling worker exposure for PROC 8b

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 95 % (inhalative).\*\*\*

## Number of the contributing scenario

9

## Contributing exposure scenario controlling worker exposure for PROC 9

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

## Number of the contributing scenario

10

## Contributing exposure scenario controlling worker exposure for PROC 15

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Exposure estimation and reference to its source

### Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

Fresh Water (Pelagic)	PEC: 0.009 mg/l; RCR: 0.104
Fresh Water (Sediment)	PEC: 0.033 mg/kg dw; RCR: 0.184
Marine Water (Pelagic)	PEC: 0.001 mg/l; RCR: 0.114
Marine Water (Sediment)	PEC: 0.004 mg/kg dw; RCR: 0.201
Agricultural Soil	PEC: 0.002 mg/kg dw; RCR: 0.146
Sewage Treatment Plant (Effluent)	PEC: 0.042 mg/l; RCR: 0.00001



# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

## Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 1	EE(inhal): 0.03
Proc 2	EE(inhal): 15.44
Proc 3	EE(inhal): 30.88
Proc 4	EE(inhal): 61.77
Proc 5	EE(inhal): 15.44
Proc 8a	EE(inhal): 15.44
Proc 8b	EE(inhal): 3.861
Proc 9	EE(inhal): 15.44
Proc 15	EE(inhal): 30.88

## Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 1	RCR(inhal): 0.0001
Proc 2	RCR(inhal): 0.05
Proc 3	RCR(inhal): 0.1
Proc 4	RCR(inhal): 0.1992
Proc 5	RCR(inhal): 0.05
Proc 8a	RCR(inhal): 0.05
Proc 8b	RCR(inhal): 0.012
Proc 9	RCR(inhal): 0.05
Proc 15	RCR(inhal): 0.1

## Number of the ES 3

Short title of the exposure scenario

## Distribution of substance

## List of use descriptors

### Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites  
SU8: Manufacture of bulk, large scale chemicals (including petroleum products)  
SU9: Manufacture of fine chemicals

### Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure  
PROC2: Use in closed, continuous process with occasional controlled exposure  
PROC3: Use in closed batch process (synthesis or formulation)  
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises  
PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities  
PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities  
PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)  
PROC15: Use as laboratory reagent

### Environmental release categories [ERC]

ERC2: Formulation of preparations (mixtures)\*\*\*

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Product characteristics

Refer to attached safety data sheets

## Processes and activities covered by the exposure scenario

Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading, distribution and associated laboratory activities.

## Further explanations

Industrial use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Assumes a good basic standard of occupational hygiene is implemented

Assumes a basic standard of occupational Health and Safety Management System\*\*\*

## Contributing Scenarios

**Number of the contributing scenario** 1  
**Contributing exposure scenario controlling environmental exposure for ERC 2\*\*\***

### Further specification

SpERC ESVOC 1.1b.v1 (ESVOC 3), release factors for (Sp)ERC were modified.\*\*\*

### Amounts used

Daily amount per site: 0.132 to

Annual amount per site: 197621 to

### Environment factors not influenced by risk management

River flow rate: 18000 m<sup>3</sup>/d Local freshwater dilution factor: 10 Local marine water dilution factor: 100

### Technical conditions and measures at process level (source) to prevent release

Release fraction to wastewater from process: 0.001 %

Release fraction to soil from process: 0.001%

Release fraction to air from process: 0.01 %\*\*\*

### Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Onsite treatment off-air. Apply vapour recovery (Adsorption, ...). Assumed Efficiency: 90 %\*\*\*

### Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m<sup>3</sup>/d): 2000

The minimum grade of elimination in the sewage plant is (%): 87.4

**Number of the contributing scenario** 2  
**Contributing exposure scenario controlling worker exposure for PROC 1**

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

**Number of the contributing scenario** 3  
**Contributing exposure scenario controlling worker exposure for PROC 2**

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

4

## Contributing exposure scenario controlling worker exposure for PROC 3

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

5

## Contributing exposure scenario controlling worker exposure for PROC 4

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

6

## Contributing exposure scenario controlling worker exposure for PROC 8a

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Frequency and duration of use

4 h (half shift)\*\*\*

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use\*\*\*

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

7

## Contributing exposure scenario controlling worker exposure for PROC 8b

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

4 h (half shift)\*\*\*

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use\*\*\*

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

8

## Contributing exposure scenario controlling worker exposure for PROC 9

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

4 h (half shift)\*\*\*

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use\*\*\*

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

9

## Contributing exposure scenario controlling worker exposure for PROC 15

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

**Technical conditions and measures to control dispersion from source towards the worker**  
provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Exposure estimation and reference to its source

### Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

Fresh Water (Pelagic)	PEC: 0.004 mg/l; RCR: 0.053
Fresh Water (Sediment)	PEC: 0.017 mg/kg dw; RCR: 0.094
Marine Water (Pelagic)	PEC: 0.0005 mg/l; RCR: 0.0063
Marine Water (Sediment)	PEC: 0.002 mg/kg dw; RCR: 0.111
Agricultural Soil	PEC: 0.002 mg/kg dw; RCR: 0.144
Sewage Treatment Plant (Effluent)	PEC: 0.0001 mg/l; RCR: 0.0000

### Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 1	EE(inhal): 0.03
Proc 2	EE(inhal): 61.77
Proc 3	EE(inhal): 77.21
Proc 4	EE(inhal): 154.4
Proc 8a	EE(inhal): 185.3
Proc 8b	EE(inhal): 92.65
Proc 9	EE(inhal): 185.3
Proc 15	EE(inhal): 30.88

### Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 1	RCR(inhal): 0.0001
Proc 2	RCR(inhal): 0.199
Proc 3	RCR(inhal): 0.2490
Proc 4	RCR(inhal): 0.498
Proc 8a	RCR(inhal): 0.598
Proc 8b	RCR(inhal): 0.299
Proc 9	RCR(inhal): 0.598
Proc 15	RCR(inhal): 0.1

## Number of the ES 4

Short title of the exposure scenario

### Uses in coatings

### List of use descriptors

### Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

## Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure  
PROC2: Use in closed, continuous process with occasional controlled exposure  
PROC3: Use in closed batch process (synthesis or formulation)  
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises  
PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)  
PROC7: Industrial spraying  
PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities  
PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities  
PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)  
PROC10: Roller application or brushing  
PROC13: Treatment of articles by dipping and pouring  
PROC15: Use as laboratory reagent

## Environmental release categories [ERC]

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

## Product characteristics

Refer to attached safety data sheets

## Processes and activities covered by the exposure scenario

Covers the use in coatings (paints, inks, adhesives, etc) within closed or contained systems including incidental exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application activities and film formation) and equipment cleaning, maintenance and associated laboratory activities.\*\*\*

## Further explanations

Industrial use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Assumes a good basic standard of occupational hygiene is implemented

## Contributing Scenarios

<b>Number of the contributing scenario</b>	<b>1</b>
<b>Contributing exposure scenario controlling environmental exposure for ERC 4</b>	

### Further specification

release factors for (Sp)ERC were modified, assessment tool used: Chesar 2.3.\*\*\*

### Amounts used

Daily amount per site: 46.01 to

Annual amount per site: 31804 to

### Environment factors not influenced by risk management

River flow rate: 18000 m<sup>3</sup>/d Local freshwater dilution factor: 10 Local marine water dilution factor: 100

### Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 0.18 %

Release fraction to wastewater from process: 0 %

Release fraction to soil from process: 0%

### Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Onsite treatment off-air; Apply air filtration - particle removal. Assumed Efficiency: 95 %\*\*\*

### Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m<sup>3</sup>/d): 2000

The minimum grade of elimination in the sewage plant is (%): 87.4

Do not apply industrial sludge to natural soils\*\*\*

<b>Number of the contributing scenario</b>	<b>2</b>
<b>Contributing exposure scenario controlling worker exposure for PROC 1</b>	

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

3

## Contributing exposure scenario controlling worker exposure for PROC 2

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

4

## Contributing exposure scenario controlling worker exposure for PROC 3

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

5

## Contributing exposure scenario controlling worker exposure for PROC 4

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

6

## Contributing exposure scenario controlling worker exposure for PROC 5

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

## Number of the contributing scenario

7

## Contributing exposure scenario controlling worker exposure for PROC 7

### Further specification

assessment tool used: StoffenManager

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Other given operational conditions affecting workers exposure

Indoor use

Room volume > 1000 m<sup>3</sup>

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).\*\*\*

### Technical conditions and measures to control dispersion from source towards the worker

Use in ventilated spray booths only.

### Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

### Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.

## Number of the contributing scenario

8

## Contributing exposure scenario controlling worker exposure for PROC 8a

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)



# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

## Number of the contributing scenario

9

## Contributing exposure scenario controlling worker exposure for PROC 8b

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 95 % (inhalative).\*\*\*

## Number of the contributing scenario

10

## Contributing exposure scenario controlling worker exposure for PROC 9

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

## Number of the contributing scenario

11

## Contributing exposure scenario controlling worker exposure for PROC 10

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

## Number of the contributing scenario

12

## Contributing exposure scenario controlling worker exposure for PROC 13

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

## Number of the contributing scenario

13

## Contributing exposure scenario controlling worker exposure for PROC 15

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Exposure estimation and reference to its source

### Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

Fresh Water (Pelagic)	PEC: 0.004 mg/l; RCR: 0.053
Fresh Water (Sediment)	PEC: 0.017 mg/kg dw; RCR: 0.094
Marine Water (Pelagic)	PEC: 0.0005 mg/l; RCR: 0.0622
Marine Water (Sediment)	PEC: 0.002 mg/kg dw; RCR: 0.111
Agricultural Soil	PEC: 0.003 mg/kg dw; RCR: 0.171
Sewage Treatment Plant (Effluent)	PEC: 0 mg/l; RCR: 0

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 1	EE(inhal): 0.031
Proc 2	EE(inhal): 15.44
Proc 3	EE(inhal): 30.88
Proc 4	EE(inhal): 61.77
Proc 5	EE(inhal): 15.44
Proc 7	EE(inhal): 0
Proc 8a	EE(inhal): 15.44
Proc 8b	EE(inhal): 3.861
Proc 9	EE(inhal): 15.44
Proc 10	EE(inhal): 15.44
Proc 13	EE(inhal): 15.44
Proc 15	EE(inhal): 30.88

## Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 1	RCR(inhal): 0.0001
Proc 2	RCR(inhal): 0.05
Proc 3	RCR(inhal): 0.1
Proc 4	RCR(inhal): 0.1992
Proc 5	RCR(inhal): 0.0498
Proc 7	RCR(inhal): 0
Proc 8a	RCR(inhal): 0.0498
Proc 8b	RCR(inhal): 0.012
Proc 9	RCR(inhal): 0.0498
Proc 10	RCR(inhal): 0.0498
Proc 13	RCR(inhal): 0.0498
Proc 15	RCR(inhal): 0.0996

\*\*\*

\*\*\*

## Number of the ES 5\*\*\*

Short title of the exposure scenario

**Uses in coatings\*\*\***

List of use descriptors \*\*\*

## Sector of uses [SU]

SU22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)\*\*\*

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure  
PROC2: Use in closed, continuous process with occasional controlled exposure  
PROC3: Use in closed batch process (synthesis or formulation)  
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises  
PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)  
PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities  
PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities  
PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)  
PROC10: Roller application or brushing  
PROC11: Non industrial spraying  
PROC13: Treatment of articles by dipping and pouring  
PROC15: Use as laboratory reagent  
PROC19: Hand-mixing with intimate contact and only PPE available\*\*\*

## Environmental release categories [ERC]

ERC8d: Wide dispersive outdoor use of processing aids in open systems\*\*\*

## Product characteristics

Refer to attached safety data sheets\*\*\*

## Processes and activities covered by the exposure scenario

Covers the use in coatings (paints, inks, adhesives, etc) within closed or contained systems including incidental exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application activities and film formation) and equipment cleaning, maintenance and associated laboratory activities.\*\*\*

## Further explanations

Professional use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Assumes a good basic standard of occupational hygiene is implemented\*\*\*

\*\*\*

## Contributing Scenarios \*\*\*

### Number of the contributing scenario

1\*\*\*

### Contributing exposure scenario controlling environmental exposure for ERC 8d\*\*\*

## Further specification

SpERC ESVOC 8.3b.v1 (ESVOC 6),  
assessment tool used:, Chesar 2.3.\*\*\*

## Amounts used

daily wide dispersive use: 0.001 to/d  
Fraction of EU tonnage used in region: 0.1  
Fraction of Regional tonnage used locally: 0.0005  
Amounts used (EU): 7700 to/a\*\*\*

## Environment factors not influenced by risk management

River flow rate: 18000 m<sup>3</sup>/d Local freshwater dilution factor: 10 Local marine water dilution factor: 100\*\*\*

## Other given operational conditions affecting environmental exposure

Indoor/Outdoor use\*\*\*

## Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 98 %  
Release fraction to wastewater from process: 1 %  
Release fraction to soil from process: 1%\*\*\*

## Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m<sup>3</sup>/d): 2000  
The minimum grade of elimination in the sewage plant is (%): 87.4\*\*\*

## Conditions and measures related to external treatment of waste for disposal

Dispose of waste product or used containers according to local regulations\*\*\*

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

\*\*\*

**Number of the contributing scenario** 2\*\*\*  
**Contributing exposure scenario controlling worker exposure for PROC 1\*\*\***

**Further specification**

assessment tool used: Chesar 2.3\*\*\*

**Product characteristics**

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)\*\*\*

**Frequency and duration of use**

8 h (full shift)\*\*\*

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use\*\*\*

**Technical conditions and measures to control dispersion from source towards the worker**

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

\*\*\*

**Number of the contributing scenario** 3\*\*\*  
**Contributing exposure scenario controlling worker exposure for PROC 2\*\*\***

**Further specification**

assessment tool used: Chesar 2.3\*\*\*

**Product characteristics**

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)\*\*\*

**Frequency and duration of use**

8 h (full shift)\*\*\*

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use\*\*\*

**Technical conditions and measures to control dispersion from source towards the worker**

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

\*\*\*

**Number of the contributing scenario** 4\*\*\*  
**Contributing exposure scenario controlling worker exposure for PROC 3\*\*\***

**Further specification**

assessment tool used: Chesar 2.3\*\*\*

**Product characteristics**

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)\*\*\*

**Frequency and duration of use**

8 h (full shift)\*\*\*

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use\*\*\*

**Technical conditions and measures to control dispersion from source towards the worker**

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

\*\*\*

**Number of the contributing scenario** 5\*\*\*  
**Contributing exposure scenario controlling worker exposure for PROC 4\*\*\***

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)\*\*\*

## Frequency and duration of use

8 h (full shift)\*\*\*

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use\*\*\*

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

\*\*\*

## Number of the contributing scenario

6\*\*\*

## Contributing exposure scenario controlling worker exposure for PROC 5\*\*\*

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)\*\*\*

## Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours\*\*\*

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use\*\*\*

\*\*\*

## Number of the contributing scenario

7\*\*\*

## Contributing exposure scenario controlling worker exposure for PROC 8a\*\*\*

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)\*\*\*

## Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours\*\*\*

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use\*\*\*

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

\*\*\*

## Number of the contributing scenario

8\*\*\*

## Contributing exposure scenario controlling worker exposure for PROC 8b\*\*\*

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)\*\*\*

## Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours\*\*\*

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use\*\*\*

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

\*\*\*

## Number of the contributing scenario

9\*\*\*

## Contributing exposure scenario controlling worker exposure for PROC 9\*\*\*

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)\*\*\*

### Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours\*\*\*

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use\*\*\*

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

\*\*\*

## Number of the contributing scenario

10\*\*\*

## Contributing exposure scenario controlling worker exposure for PROC 10\*\*\*

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)\*\*\*

### Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours\*\*\*

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use\*\*\*

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

\*\*\*

## Number of the contributing scenario

11\*\*\*

## Contributing exposure scenario controlling worker exposure for PROC 11\*\*\*

### Further specification

assessment tool used: StoffenManager\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)\*\*\*

### Frequency and duration of use

8 h (full shift)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor use

Room volume > 1000 m<sup>3</sup>

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).\*\*\*

## Technical conditions and measures to control dispersion from source towards the worker

Use in ventilated spray booths only.\*\*\*

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day  
Ensure the ventilation system is regularly maintained and tested\*\*\*

## Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.\*\*\*

\*\*\*

**Number of the contributing scenario** 12\*\*\*  
**Contributing exposure scenario controlling worker exposure for PROC 11\*\*\***

### Further specification

assessment tool used: StoffenManager\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)\*\*\*

### Frequency and duration of use

Exposure time per day: 6 h/d\*\*\*

### Other given operational conditions affecting workers exposure

Indoor use

Room volume 100 - 1000 m<sup>3</sup>

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Ensure that the task is not carried out by more than one worker simultaneously.\*\*\*

### Technical conditions and measures to control dispersion from source towards the worker

Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 47 % (inhalative).\*\*\*

## Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day  
Ensure the ventilation system is regularly maintained and tested\*\*\*

## Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.\*\*\*

\*\*\*

**Number of the contributing scenario** 13\*\*\*  
**Contributing exposure scenario controlling worker exposure for PROC 11\*\*\***

### Further specification

assessment tool used: StoffenManager\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)\*\*\*

### Frequency and duration of use

8 h (full shift)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor use

Room volume < 100 m<sup>3</sup>

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Ensure that the task is not carried out by more than one worker simultaneously.\*\*\*

### Technical conditions and measures to control dispersion from source towards the worker

Provide enhanced general ventilation by mechanical means. Effectiveness of LEV (local exhaust ventilation): 47 % (inhalative).\*\*\*

## Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day  
Ensure the ventilation system is regularly maintained and tested\*\*\*

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear respiratory protection (Efficiency: 80 %) Alternatively: Use duration max. 5 h. Inspect and clean equipment regularly.\*\*\*

\*\*\*

**Number of the contributing scenario** 14\*\*\*  
**Contributing exposure scenario controlling worker exposure for PROC 13\*\*\***



# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)\*\*\*

## Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours\*\*\*

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use\*\*\*

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

\*\*\*

## Number of the contributing scenario

15\*\*\*

## Contributing exposure scenario controlling worker exposure for PROC 15\*\*\*

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)\*\*\*

## Frequency and duration of use

8 h (full shift)\*\*\*

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use\*\*\*

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

\*\*\*

## Number of the contributing scenario

16\*\*\*

## Contributing exposure scenario controlling worker exposure for PROC 19\*\*\*

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)\*\*\*

## Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours\*\*\*

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 1980 cm<sup>2</sup>\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use\*\*\*

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

\*\*\*

\*\*\*

## Exposure estimation and reference to its source \*\*\*

## Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio\*\*\*

Fresh Water (Pelagic)	PEC: 0.004 mg/l; RCR: 0.054***
Fresh Water (Sediment)	PEC: 0.017 mg/kg dw; RCR: 0.095***
Marine Water (Pelagic)	PEC: 0.0005 mg/l; RCR: 0.0630***
Marine Water (Sediment)	PEC: 0.002 mg/kg dw; RCR: 0.112***
Agricultural Soil	PEC: 0.0006 mg/kg dw; RCR: 0.04***

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

Version / Revision 3 .00\*\*\*

Sewage Treatment Plant (Effluent) PEC: 0.0007 mg/l; RCR: 0.0000\*\*\*

## Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]. The RMMs described above suffice to control risks for both local and systemic effects.\*\*\*

Proc 1	EE(inhal): 0.031***
Proc 2	EE(inhal): 61.77***
Proc 3	EE(inhal): 77.21***
Proc 4	EE(inhal): 154.4***
Proc 5	EE(inhal): 185.3***
Proc 8a	EE(inhal): 185.3***
Proc 8b	EE(inhal): 92.65***
Proc 9	EE(inhal): 185.3***
Proc 10	EE(inhal): 185.3***
Proc 11	EE(inhal): 0 - Contributing Scenario 11 EE(inhal): 300 - Contributing Scenario 12 EE(inhal): 187.5 - Contributing Scenario 13***
Proc 13	EE(inhal): 185.3***
Proc 15	EE(inhal): 30.88***
Proc 19	EE(inhal): 185.3***

## Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.\*\*\*

Proc 1	RCR(inhal): 0.0001***
Proc 2	RCR(inhal): 0.1992***
Proc 3	RCR(inhal): 0.2490***
Proc 4	RCR(inhal): 0.4980***
Proc 5	RCR(inhal): 0.5976***
Proc 8a	RCR(inhal): 0.5976***
Proc 8b	RCR(inhal): 0.2988***
Proc 9	RCR(inhal): 0.5976***
Proc 10	RCR(inhal): 0.5976***
Proc 11	RCR(inhal): 0 - Contributing Scenarios 11 RCR(inhal): 0.9677 - Contributing Scenarios 12 RCR(inhal): 0.6048 - Contributing Scenarios 13***
Proc 13	RCR(inhal): 0.5976***
Proc 15	RCR(inhal): 0.0996***
Proc 19	RCR(inhal): 0.5976***

\*\*\*

## Number of the ES 6

Short title of the exposure scenario

**Use in Cleaning Products**

### List of use descriptors

### Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

## Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure  
PROC2: Use in closed, continuous process with occasional controlled exposure  
PROC3: Use in closed batch process (synthesis or formulation)  
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises  
PROC7: Industrial spraying  
PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities  
PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities  
PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)  
PROC10: Roller application or brushing  
PROC13: Treatment of articles by dipping and pouring

## Environmental release categories [ERC]

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

## Product characteristics

Refer to attached safety data sheets

## Processes and activities covered by the exposure scenario

Covers the use as a component of cleaning products including transfer from storage, pouring/unloading from drums or containers. exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand), related equipment cleaning and maintenance.

## Further explanations

Industrial use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Assumes a good basic standard of occupational hygiene is implemented

## Contributing Scenarios

**Number of the contributing scenario** 1

**Contributing exposure scenario controlling environmental exposure for ERC 4**

### Further specification

SpERC ESVOC 4.4a.v1 (ESVOC 8), release factors for (Sp)ERC were modified, assessment tool used: Chesar 2.3.\*\*\*

### Amounts used

Daily amount per site: 106.8 to

Annual amount per site: 2136 to

### Environment factors not influenced by risk management

River flow rate: 18000 m<sup>3</sup>/d Local freshwater dilution factor: 10 Local marine water dilution factor: 100

### Technical conditions and measures at process level (source) to prevent release

Release fraction to wastewater from process: 0.003 %

Release fraction to soil from process: 0%

Release fraction to air from process: 0.1 %\*\*\*

### Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Onsite treatment off-air. Upgrade Systems in place or implement additional treatment. Assumed Efficiency: 99.9 % Onsite treatment wastewater. Apply acclimated biological treatment. Assumed Efficiency: 70 %\*\*\*

### Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m<sup>3</sup>/d): 2000

The minimum grade of elimination in the sewage plant is (%): 87.4

**Number of the contributing scenario** 2

**Contributing exposure scenario controlling worker exposure for PROC 1**

### Further specification

assessment tool used: Chesar 2.3\*\*\*

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

Version / Revision 3 .00\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

**Number of the contributing scenario 3**  
**Contributing exposure scenario controlling worker exposure for PROC 2**

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

**Number of the contributing scenario 4**  
**Contributing exposure scenario controlling worker exposure for PROC 3**

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

**Number of the contributing scenario 5**  
**Contributing exposure scenario controlling worker exposure for PROC 4**

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

6

## Contributing exposure scenario controlling worker exposure for PROC 7

### Further specification

assessment tool used: StoffenManager

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

## Other given operational conditions affecting workers exposure

Indoor use

Room volume > 1000 m<sup>3</sup>

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).\*\*\*

## Technical conditions and measures to control dispersion from source towards the worker

Use in ventilated spray booths only.

## Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested\*\*\*

## Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.

## Number of the contributing scenario

7

## Contributing exposure scenario controlling worker exposure for PROC 8a

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

## Number of the contributing scenario

8

## Contributing exposure scenario controlling worker exposure for PROC 8b

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 95 % (inhalative).\*\*\*

## Number of the contributing scenario

9

## Contributing exposure scenario controlling worker exposure for PROC 9

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

## Number of the contributing scenario

10

## Contributing exposure scenario controlling worker exposure for PROC 10

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

## Number of the contributing scenario

11

## Contributing exposure scenario controlling worker exposure for PROC 13

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

## Other given operational conditions affecting workers exposure

Indoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

## Exposure estimation and reference to its source

### Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

Fresh Water (Pelagic)	PEC: 0.0024 mg/l; RCR: 0.298
Fresh Water (Sediment)	PEC: 0.094 mg/kg dw; RCR: 0.528
Marine Water (Pelagic)	PEC: 0.003 mg/l; RCR: 0.308
Marine Water (Sediment)	PEC: 0.01 mg/kg dw; RCR: 0.545
Agricultural Soil	PEC: 0.0008 mg/kg dw; RCR: 0.051
Sewage Treatment Plant (Effluent)	PEC: 0.201 mg/l; RCR: 0.0001

### Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 1	EE(inhal): 0.031
Proc 2	EE(inhal): 15.44
Proc 3	EE(inhal): 30.88
Proc 4	EE(inhal): 61.77
Proc 7	EE(inhal): 0
Proc 8a	EE(inhal): 15.44
Proc 8b	EE(inhal): 3.861
Proc 9	EE(inhal): 15.44
Proc 10	EE(inhal): 15.44
Proc 13	EE(inhal): 15.44

### Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 1	RCR(inhal): 0.0001
Proc 2	RCR(inhal): 0.05
Proc 3	RCR(inhal): 0.1
Proc 4	RCR(inhal): 0.1992
Proc 7	RCR(inhal): 0
Proc 8a	RCR(inhal): 0.05
Proc 8b	RCR(inhal): 0.012
Proc 9	RCR(inhal): 0.0498
Proc 10	RCR(inhal): 0.0498
Proc 13	RCR(inhal): 0.0498

## Number of the ES 7

Short title of the exposure scenario

### Use in Cleaning Products

#### List of use descriptors

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

## Sector of uses [SU]

SU22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

## Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC10: Roller application or brushing

PROC11: Non industrial spraying

PROC13: Treatment of articles by dipping and pouring

## Environmental release categories [ERC]

ERC8d: Wide dispersive outdoor use of processing aids in open systems

## Product characteristics

Refer to attached safety data sheets

## Processes and activities covered by the exposure scenario

Covers the use as a component of cleaning products including pouring/unloading from drums or containers; and exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand).

## Further explanations

Professional use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Assumes a good basic standard of occupational hygiene is implemented

## Contributing Scenarios

### Number of the contributing scenario

1

### Contributing exposure scenario controlling environmental exposure for ERC 8d

#### Further specification

SpERC ESVOC 8.4b.v1 (ESVOC 9),  
assessment tool used: Chesar 2.3.\*\*\*

#### Amounts used

daily wide dispersive use: 0.0001 to/d

Fraction of EU tonnage used in region: 0.1

Fraction of Regional tonnage used locally: 0.0005

Amounts used (EU): 720 to/a

#### Frequency and duration of use

Covers use up to: 365 days\*\*\*

#### Environment factors not influenced by risk management

River flow rate: 18000 m<sup>3</sup>/d Local freshwater dilution factor: 10 Local marine water dilution factor: 100

#### Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 2 %

Release fraction to wastewater from process: 0.0001 %

Release fraction to soil from process: 0%

#### Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m<sup>3</sup>/d): 2000

The minimum grade of elimination in the sewage plant is (%): 87.4

### Number of the contributing scenario

2



# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Contributing exposure scenario controlling worker exposure for PROC 1

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

Number of the contributing scenario 3

## Contributing exposure scenario controlling worker exposure for PROC 2

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

Number of the contributing scenario 4

## Contributing exposure scenario controlling worker exposure for PROC 3

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

Number of the contributing scenario 5

## Contributing exposure scenario controlling worker exposure for PROC 4

### Further specification

assessment tool used: Chesar 2.3\*\*\*

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

6

## Contributing exposure scenario controlling worker exposure for PROC 8a

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

7

## Contributing exposure scenario controlling worker exposure for PROC 8b

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

8

## Contributing exposure scenario controlling worker exposure for PROC 9

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

**Number of the contributing scenario** 9  
**Contributing exposure scenario controlling worker exposure for PROC 10**

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

**Number of the contributing scenario** 10  
**Contributing exposure scenario controlling worker exposure for PROC 11**

## Further specification

assessment tool used: StoffenManager

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Other given operational conditions affecting workers exposure

Indoor use

Room volume > 1000 m<sup>3</sup>

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).\*\*\*

## Technical conditions and measures to control dispersion from source towards the worker

Use in ventilated spray booths only.

## Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested\*\*\*

## Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.

**Number of the contributing scenario** 11  
**Contributing exposure scenario controlling worker exposure for PROC 11**

## Further specification

assessment tool used: StoffenManager

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

Exposure time per day: 6 h/d

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

## Other given operational conditions affecting workers exposure

Indoor use

Room volume 100 - 1000 m<sup>3</sup>

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).\*\*\*

## Technical conditions and measures to control dispersion from source towards the worker

Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 47 % (inhalative).\*\*\*

## Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested\*\*\*

## Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.

## Number of the contributing scenario

12

## Contributing exposure scenario controlling worker exposure for PROC 11

### Further specification

assessment tool used: StoffenManager

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

## Other given operational conditions affecting workers exposure

Indoor use

Room volume < 100 m<sup>3</sup>

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Ensure that the task is not carried out by more than one worker simultaneously.\*\*\*

## Technical conditions and measures to control dispersion from source towards the worker

Provide enhanced general ventilation by mechanical means. Effectiveness of LEV (local exhaust ventilation): 47 % (inhalative).\*\*\*

## Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested\*\*\*

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear respiratory protection (Efficiency: 80 %) Alternatively: Use duration max. 5 h. Inspect and clean equipment regularly.

## Number of the contributing scenario

13

## Contributing exposure scenario controlling worker exposure for PROC 13

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Exposure estimation and reference to its source

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

## Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

Fresh Water (Pelagic)	PEC: 0.004 mg/l; RCR: 0.053
Fresh Water (Sediment)	PEC: 0.017 mg/kg dw; RCR: 0.094
Marine Water (Pelagic)	PEC: 0.0005 mg/l; RCR: 0.063
Marine Water (Sediment)	PEC: 0.002 mg/kg dw; RCR: 0.111
Agricultural Soil	PEC: 0.0006 mg/kg dw; RCR: 0.04
Sewage Treatment Plant (Effluent)	PEC: 0.0000 mg/l; RCR: 0.0000

## Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 1	EE(inhal): 0.031
Proc 2	EE(inhal): 61.75
Proc 3	EE(inhal): 77.21
Proc 4	EE(inhal): 154.4
Proc 8a	EE(inhal): 185.3
Proc 8b	EE(inhal): 92.65
Proc 9	EE(inhal): 185.3
Proc 10	EE(inhal): 185.3
Proc 11	EE(inhal): 0 - Contributing Scenario 10 EE(inhal): 300 - Contributing Scenario 11 EE(inhal): 187.5 - Contributing Scenario 12
Proc 13	EE(inhal): 185.3

## Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 1	RCR(inhal): 0.0001
Proc 2	RCR(inhal): 0.199
Proc 3	RCR(inhal): 0.2490
Proc 4	RCR(inhal): 0.498
Proc 8a	RCR(inhal): 0.598
Proc 8b	RCR(inhal): 0.299
Proc 9	RCR(inhal): 0.598
Proc 10	RCR(inhal): 0.598
Proc 11	RCR(inhal): 0 - Contributing Scenarios 10 RCR(inhal): 0.968 - Contributing Scenarios 11 RCR(inhal): 0.605 - Contributing Scenarios 12
Proc 13	RCR(inhal): 0.598

## Number of the ES 8

Short title of the exposure scenario

**lubricants**

## List of use descriptors

### Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

## Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure  
PROC2: Use in closed, continuous process with occasional controlled exposure  
PROC3: Use in closed batch process (synthesis or formulation)  
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises  
PROC7: Industrial spraying  
PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities  
PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities  
PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)  
PROC10: Roller application or brushing  
PROC13: Treatment of articles by dipping and pouring  
PROC17: Lubrication at high energy conditions and in partly open process  
PROC18: Greasing at high energy conditions

## Environmental release categories [ERC]

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

## Product characteristics

Refer to attached safety data sheets

## Processes and activities covered by the exposure scenario

Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of machinery/engines and similar articles, reworking on reject articles, equipment maintenance and disposal of wastes.

## Further explanations

Industrial use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Assumes a good basic standard of occupational hygiene is implemented

## Contributing Scenarios

<b>Number of the contributing scenario</b>	<b>1</b>
<b>Contributing exposure scenario controlling environmental exposure for ERC 4</b>	

### Further specification

A&B Tables: A3.8, B3.7,

assessment tool used: Chesar 2.3.\*\*\*

### Amounts used

Daily amount per site: 1.45 to

Annual amount per site: 506 to

### Environment factors not influenced by risk management

River flow rate: 18000 m<sup>3</sup>/d Local freshwater dilution factor: 100 Local marine water dilution factor: 10 3

### Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 0.5 %

Release fraction to wastewater from process: 0.05 %

Release fraction to soil from process: 0.1%

### Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m<sup>3</sup>/d): 2000

The minimum grade of elimination in the sewage plant is (%): 87.4

<b>Number of the contributing scenario</b>	<b>2</b>
<b>Contributing exposure scenario controlling worker exposure for PROC 1</b>	

### Further specification

assessment tool used: Chesar 2.3\*\*\*

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

Version / Revision 3 .00\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

**Number of the contributing scenario 3**  
**Contributing exposure scenario controlling worker exposure for PROC 2**

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

**Number of the contributing scenario 4**  
**Contributing exposure scenario controlling worker exposure for PROC 3**

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

**Number of the contributing scenario 5**  
**Contributing exposure scenario controlling worker exposure for PROC 4**

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

6

## Contributing exposure scenario controlling worker exposure for PROC 7

### Further specification

assessment tool used: StoffenManager

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

Room volume > 1000 m<sup>3</sup>

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).\*\*\*

## Technical conditions and measures to control dispersion from source towards the worker

Use in ventilated spray booths only.

## Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested\*\*\*

## Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.

## Number of the contributing scenario

7

## Contributing exposure scenario controlling worker exposure for PROC 8a

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

## Number of the contributing scenario

8

## Contributing exposure scenario controlling worker exposure for PROC 8b

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)



# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 95 % (inhalative).\*\*\*

## Number of the contributing scenario

9

## Contributing exposure scenario controlling worker exposure for PROC 9

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

## Number of the contributing scenario

10

## Contributing exposure scenario controlling worker exposure for PROC 10

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

## Number of the contributing scenario

11

## Contributing exposure scenario controlling worker exposure for PROC 13

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Other given operational conditions affecting workers exposure

Indoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

**Number of the contributing scenario** 12  
**Contributing exposure scenario controlling worker exposure for PROC 17**

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

**Number of the contributing scenario** 13  
**Contributing exposure scenario controlling worker exposure for PROC 17**

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure > 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor use

Operation is carried out at elevated temperature (> 20°C above ambient temperature)

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

**Number of the contributing scenario** 14  
**Contributing exposure scenario controlling worker exposure for PROC 18**

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

**Technical conditions and measures to control dispersion from source towards the worker**  
provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

**Number of the contributing scenario** 15  
**Contributing exposure scenario controlling worker exposure for PROC 18**

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure > 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor use

Operation is carried out at elevated temperature (> 20°C above ambient temperature)

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

## Exposure estimation and reference to its source

### Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

Fresh Water (Pelagic)	PEC: 0.009 mg/l; RCR: 0.108
Fresh Water (Sediment)	PEC: 0.034 mg/kg dw; RCR: 0.192
Marine Water (Pelagic)	PEC: 0.001 mg/l; RCR: 0.118
Marine Water (Sediment)	PEC: 0.004 mg/kg dw; RCR: 0.209
Agricultural Soil	PEC: 0.001 mg/kg dw; RCR: 0.066
Sewage Treatment Plant (Effluent)	PEC: 0.045 mg/l; RCR: 0.000

### Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 1	EE(inhal): 0.031
Proc 2	EE(inhal): 15.44
Proc 3	EE(inhal): 30.88
Proc 4	EE(inhal): 61.77
Proc 7	EE(inhal): 0
Proc 8a	EE(inhal): 15.44
Proc 8b	EE(inhal): 3.861
Proc 9	EE(inhal): 15.44
Proc 10	EE(inhal): 15.44
Proc 13	EE(inhal): 15.44
Proc 17	EE(inhal): 154.4 - Contributing Scenario 12 EE(inhal): 30.88 - Contributing Scenario 13
Proc 18	EE(inhal): 154.4 - Contributing Scenario 14 EE(inhal): 30.88 - Contributing Scenario 15

### Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

Proc 1	RCR(inhal): 0.0001
Proc 2	RCR(inhal): 0.05
Proc 3	RCR(inhal): 0.1
Proc 4	RCR(inhal): 0.1992
Proc 7	RCR(inhal): 0.0000
Proc 8a	RCR(inhal): 0.05
Proc 8b	RCR(inhal): 0.012
Proc 9	RCR(inhal): 0.05
Proc 10	RCR(inhal): 0.05
Proc 13	RCR(inhal): 0.05
Proc 17	RCR(inhal): 0.4980 - Contributing Scenarios 12 RCR(inhal): 0.1 - Contributing Scenarios 13
Proc 18	RCR(inhal): 0.4980 - Contributing Scenarios 14 RCR(inhal): 0.1 - Contributing Scenarios 15

## Number of the ES 9

Short title of the exposure scenario

**lubricants**

### List of use descriptors

#### Sector of uses [SU]

SU22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC10: Roller application or brushing

PROC11: Non industrial spraying

PROC13: Treatment of articles by dipping and pouring

PROC17: Lubrication at high energy conditions and in partly open process

PROC18: Greasing at high energy conditions

PROC20: Heat and pressure transfer fluids in dispersive, professional use but closed systems

#### Environmental release categories [ERC]

ERC9b: Wide dispersive outdoor use of substances in closed systems

#### Product characteristics

Refer to attached safety data sheets

#### Processes and activities covered by the exposure scenario

Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of engines and similar articles, reworking on reject articles, equipment maintenance and disposal of waste oil.

#### Further explanations

Professional use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Assumes a good basic standard of occupational hygiene is implemented

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Contributing Scenarios

**Number of the contributing scenario** 1  
**Contributing exposure scenario controlling environmental exposure for ERC 9b**

### Further specification

SpERC ESVOC 9.6b.v1 (ESVOC 14), SpERC ESVOC 9.6d.v1 (ESVOC 16),  
assessment tool used: Chesar 2.3.\*\*\*

### Amounts used

daily wide dispersive use: 0.00001 to/d  
Amounts used (EU): 93 to/a  
Fraction of EU tonnage used in region: 0.1  
Fraction of Regional tonnage used locally: 0.0005

### Frequency and duration of use

Covers use up to: 365 days\*\*\*

### Environment factors not influenced by risk management

River flow rate: 18000 m<sup>3</sup>/d  
Local freshwater dilution factor: 10  
Local marine water dilution factor: 100  
**Technical conditions and measures at process level (source) to prevent release**  
Release fraction to air from process: 1 %  
Release fraction to wastewater from process: 1 %  
Release fraction to soil from process: 1%

### Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m<sup>3</sup>/d): 2000  
The minimum grade of elimination in the sewage plant is (%): 87.4

**Number of the contributing scenario** 2  
**Contributing exposure scenario controlling worker exposure for PROC 1**

### Further specification

assessment tool used: Chesar 2.3.\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP  
Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

**Number of the contributing scenario** 3  
**Contributing exposure scenario controlling worker exposure for PROC 2**

### Further specification

assessment tool used: Chesar 2.3.\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP  
Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

**Number of the contributing scenario** 4  
**Contributing exposure scenario controlling worker exposure for PROC 3**

#### Further specification

assessment tool used: Chesar 2.3\*\*\*

#### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

#### Frequency and duration of use

8 h (full shift)

#### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

#### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

**Number of the contributing scenario** 5  
**Contributing exposure scenario controlling worker exposure for PROC 4**

#### Further specification

assessment tool used: Chesar 2.3\*\*\*

#### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

#### Frequency and duration of use

8 h (full shift)

#### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

#### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

**Number of the contributing scenario** 6  
**Contributing exposure scenario controlling worker exposure for PROC 8a**

#### Further specification

assessment tool used: Chesar 2.3\*\*\*

#### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

#### Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

#### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

#### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

**Number of the contributing scenario** 7

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Contributing exposure scenario controlling worker exposure for PROC 8b

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

8

## Contributing exposure scenario controlling worker exposure for PROC 9

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

9

## Contributing exposure scenario controlling worker exposure for PROC 10

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

10

## Contributing exposure scenario controlling worker exposure for PROC 11

### Further specification

assessment tool used: StoffenManager

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Other given operational conditions affecting workers exposure

Indoor use

Room volume > 1000 m3

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).\*\*\*

## Technical conditions and measures to control dispersion from source towards the worker

Use in ventilated spray booths only.

## Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested\*\*\*

## Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.

## Number of the contributing scenario

11\*\*\*

## Contributing exposure scenario controlling worker exposure for PROC 11

### Further specification

assessment tool used: StoffenManager

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

Exposure time per day: 6 h/d

### Other given operational conditions affecting workers exposure

Indoor use

Room volume 100 - 1000 m3

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Ensure that the task is not carried out by more than one worker simultaneously.\*\*\*

### Technical conditions and measures to control dispersion from source towards the worker

Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 47 % (inhalative).\*\*\*

### Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested\*\*\*

### Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.

## Number of the contributing scenario

12\*\*\*

## Contributing exposure scenario controlling worker exposure for PROC 11

### Further specification

assessment tool used: StoffenManager\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor use

Room volume < 100 m3

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Ensure that the task is not carried out by more than one worker simultaneously.\*\*\*



# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Technical conditions and measures to control dispersion from source towards the worker

Provide enhanced general ventilation by mechanical means. Effectiveness of LEV (local exhaust ventilation): 47 % (inhalative).\*\*\*

## Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day  
Ensure the ventilation system is regularly maintained and tested\*\*\*

## Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly. Wear respiratory protection (Efficiency: 80 %) Alternatively: Use duration max. 5 h.

**Number of the contributing scenario** 13  
**Contributing exposure scenario controlling worker exposure for PROC 13**

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP  
Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

**Number of the contributing scenario** 14  
**Contributing exposure scenario controlling worker exposure for PROC 17**

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP  
Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)\*\*\*

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use\*\*\*

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear respiratory protection (Efficiency: 90 %) Alternatively: Use duration max. 1 h.\*\*\*

**Number of the contributing scenario** 15  
**Contributing exposure scenario controlling worker exposure for PROC 17**

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)  
Liquid, vapour pressure 0,5 - 10 kPa at STP\*\*\*

### Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours\*\*\*

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Other given operational conditions affecting workers exposure

Indoor use

Operation is carried out at elevated temperature (> 20°C above ambient temperature)

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 80 % (inhalative).\*\*\*

### Conditions and measures related to personal protection, hygiene and health evaluation

If above technical/organisational control measures are not feasible, then adopt following PPE. If carried out for more than 1h, wear respiratory protection (efficiency 90%).\*\*\*

**Number of the contributing scenario** 16  
**Contributing exposure scenario controlling worker exposure for PROC 18\*\*\***

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)\*\*\*

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor use\*\*\*

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 80 % (inhalative). If no adequate ventilation is available, avoid carrying out operations for more than 1 h.\*\*\*

**Number of the contributing scenario** 17  
**Contributing exposure scenario controlling worker exposure for PROC 18\*\*\***

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP\*\*\*

### Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours\*\*\*

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor use

Operation is carried out at elevated temperature (> 20°C above ambient temperature)\*\*\*

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 80 % (inhalative).\*\*\*

### Conditions and measures related to personal protection, hygiene and health evaluation

If above technical/organisational control measures are not feasible, then adopt following PPE. If carried out for more than 1h, wear respiratory protection (efficiency 90%).\*\*\*

**Number of the contributing scenario** 18  
**Contributing exposure scenario controlling worker exposure for PROC 20\*\*\***

### Further specification

assessment tool used: Chesar 2.3\*\*\*

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use\*\*\*

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Exposure estimation and reference to its source

### Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

Fresh Water (Pelagic)	PEC: 0.004 mg/l; RCR: 0.053
Fresh Water (Sediment)	PEC: 0.017 mg/kg dw; RCR: 0.094
Marine Water (Pelagic)	PEC: 0.0005 mg/l; RCR: 0.063
Marine Water (Sediment)	PEC: 0.002 mg/kg dw; RCR: 0.111
Agricultural Soil	PEC: 0.0006 mg/kg dw; RCR: 0.04
Sewage Treatment Plant (Effluent)	PEC: 0.0000 mg/l; RCR: 0.0000

### Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 1	EE(inhal): 0.031
Proc 2	EE(inhal): 61.77
Proc 3	EE(inhal): 77.21
Proc 4	EE(inhal): 154.4
Proc 8a	EE(inhal): 185.3
Proc 8b	EE(inhal): 92.65
Proc 9	EE(inhal): 185.3
Proc 10	EE(inhal): 185.3
Proc 11	EE(inhal): 0 - Contributing Scenario 10 EE(inhal): 300 - Contributing Scenario 11 EE(inhal): 187.50 - Contributing Scenario 12
Proc 13	EE(inhal): 185.3
Proc 17	EE(inhal): 185.3 - Contributing Scenario 14 EE(inhal): 123.5 - Contributing Scenario 15
Proc 18	EE(inhal): 123.50 - Contributing Scenario 16 EE(inhal): 185.3 - Contributing Scenario 17
Proc 20	EE(inhal): 61.77

### Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 1	RCR(inhal): 0.0001
Proc 2	RCR(inhal): 0.199
Proc 3	RCR(inhal): 0.249
Proc 4	RCR(inhal): 0.498
Proc 8a	RCR(inhal): 0.598
Proc 8b	RCR(inhal): 0.299
Proc 9	RCR(inhal): 0.598
Proc 10	RCR(inhal): 0.598

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

Proc 11	RCR(inhal): 0 - Contributing Scenarios 10 RCR(inhal): 0.968 - Contributing Scenarios 11 RCR(inhal): 0.605 - Contributing Scenarios 12
Proc 13	RCR(inhal): 0.598
Proc 17	RCR(inhal): 0.399 - Contributing Scenarios 14 RCR(inhal): 0.598 - Contributing Scenarios 15
Proc 18	RCR(inhal): 0.399 - Contributing Scenarios 16 RCR(inhal): 0.598 - Contributing Scenarios 17
Proc 20	RCR(inhal): 0.199

## Number of the ES 10

Short title of the exposure scenario

**Metal working fluids / rolling oils**

### List of use descriptors

#### Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites

#### Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC7: Industrial spraying

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC10: Roller application or brushing

PROC13: Treatment of articles by dipping and pouring

PROC17: Lubrication at high energy conditions and in partly open process

#### Environmental release categories [ERC]

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

#### Product characteristics

Refer to attached safety data sheets

#### Processes and activities covered by the exposure scenario

Covers the use in formulated MWFs (MWFs) including transfer operations, open and contained cutting/machining activities, automated and manual application of corrosion protections, draining and working on contaminated/ reject articles, and disposal of waste oils.\*\*\*

#### Further explanations

Industrial use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Assumes a good basic standard of occupational hygiene is implemented

### Contributing Scenarios

**Number of the contributing scenario**

**1**

**Contributing exposure scenario controlling environmental exposure for  
ERC 4**

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Further specification

SpERC ESVOC 4.7a.v1 (ESVOC 18), release factors for (Sp)ERC were modified, assessment tool used: Chesar 2.3.\*\*\*

## Amounts used

Daily amount per site: 2 to

Annual amount per site: 40 to

Fraction of EU tonnage used in region: 100\*\*\*

## Environment factors not influenced by risk management

River flow rate: 18000 m<sup>3</sup>/d

Local freshwater dilution factor: 10

Local marine water dilution factor: 100

## Technical conditions and measures at process level (source) to prevent release

Release fraction to wastewater from process: 0.03 %

Release fraction to soil from process: 0%

Release fraction to air from process: 0.6 %\*\*\*

## Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Onsite treatment off-air. Upgrade Systems in place or implement additional treatment. Assumed Efficiency: 70 % Onsite treatment wastewater. Apply acclimated biological treatment. Assumed Efficiency: 70 %\*\*\*

## Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m<sup>3</sup>/d): 2000

The minimum grade of elimination in the sewage plant is (%): 87.4

## Conditions and measures related to external treatment of waste for disposal

Dispose of waste product or used containers according to local regulations\*\*\*

## Number of the contributing scenario

2

### Contributing exposure scenario controlling worker exposure for PROC 1

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

3

### Contributing exposure scenario controlling worker exposure for PROC 2

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

**Number of the contributing scenario** 4  
**Contributing exposure scenario controlling worker exposure for PROC 3**

**Further specification**

assessment tool used: Chesar 2.3\*\*\*

**Product characteristics**

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

**Other given operational conditions affecting workers exposure**

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

**Number of the contributing scenario** 5  
**Contributing exposure scenario controlling worker exposure for PROC 5\*\*\***

**Further specification**

assessment tool used: Chesar 2.3\*\*\*

**Product characteristics**

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

**Other given operational conditions affecting workers exposure**

Indoor use\*\*\*

**Technical conditions and measures to control dispersion from source towards the worker**

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

**Number of the contributing scenario** 6  
**Contributing exposure scenario controlling worker exposure for PROC 7**

**Further specification**

assessment tool used: StoffenManager\*\*\*

**Product characteristics**

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

**Frequency and duration of use**

8 h (full shift)

**Other given operational conditions affecting workers exposure**

Indoor use

Room volume > 1000 m<sup>3</sup>

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).\*\*\*

**Technical conditions and measures to control dispersion from source towards the worker**

Use in ventilated spray booths only.

**Organisational measures to prevent /limit releases, dispersion and exposure**

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested\*\*\*

**Conditions and measures related to personal protection, hygiene and health evaluation**

Inspect and clean equipment regularly.

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

**Number of the contributing scenario** 7  
**Contributing exposure scenario controlling worker exposure for PROC 8a**

**Further specification**

assessment tool used: Chesar 2.3\*\*\*

**Product characteristics**

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

**Other given operational conditions affecting workers exposure**

Indoor use

**Technical conditions and measures to control dispersion from source towards the worker**

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

**Number of the contributing scenario** 9  
**Contributing exposure scenario controlling worker exposure for PROC 8b**

**Further specification**

assessment tool used: Chesar 2.3\*\*\*

**Product characteristics**

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

**Other given operational conditions affecting workers exposure**

Indoor use

**Technical conditions and measures to control dispersion from source towards the worker**

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 95 % (inhalative).\*\*\*

**Number of the contributing scenario** 10  
**Contributing exposure scenario controlling worker exposure for PROC 9**

**Further specification**

assessment tool used: Chesar 2.3\*\*\*

**Product characteristics**

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

**Frequency and duration of use**

8 h (full shift)

**Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

**Other given operational conditions affecting workers exposure**

Indoor use

**Technical conditions and measures to control dispersion from source towards the worker**

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

**Number of the contributing scenario** 11

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Contributing exposure scenario controlling worker exposure for PROC 10

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

## Number of the contributing scenario

12

## Contributing exposure scenario controlling worker exposure for PROC 13

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).\*\*\*

## Number of the contributing scenario

13

## Contributing exposure scenario controlling worker exposure for PROC 17

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

14

## Contributing exposure scenario controlling worker exposure for PROC 17



# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure > 10 kPa at STP

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Operation is carried out at elevated temperature (> 20°C above ambient temperature)

Indoor and outdoor use\*\*\*

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear respiratory protection (Efficiency: 95 %).\*\*\*

## Exposure estimation and reference to its source

### Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

Fresh Water (Pelagic)	PEC: 0.008 mg/l; RCR: 0.099
Fresh Water (Sediment)	PEC: 0.031 mg/kg dw; RCR: 0.175
Marine Water (Pelagic)	PEC: 0.0009 mg/l; RCR: 0.109
Marine Water (Sediment)	PEC: 0.003 mg/kg dw; RCR: 0.192
Agricultural Soil	PEC: 0.0008 mg/kg dw; RCR: 0.051
Sewage Treatment Plant (Effluent)	PEC: 0.038 mg/l; RCR: 0.00001

### Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 1	EE(inhal): 0.031
Proc 2	EE(inhal): 15.44
Proc 3	EE(inhal): 30.88
Proc 5	EE(inhal): 15.44
Proc 7	EE(inhal): 0
Proc 8a	EE(inhal): 15.44
Proc 8b	EE(inhal): 3.861
Proc 9	EE(inhal): 15.44
Proc 10	EE(inhal): 15.44
Proc 13	EE(inhal): 15.44
Proc 17	EE(inhal): 154.38 - Contributing Scenario 13 EE(inhal): 15.44 - Contributing Scenario 14

### Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 1	RCR(inhal): 0.0001
Proc 2	RCR(inhal): 0.05
Proc 3	RCR(inhal): 0.100
Proc 5	RCR(inhal): 0.05
Proc 7	RCR(inhal): 0
Proc 8a	RCR(inhal): 0.05
Proc 8b	RCR(inhal): 0.012
Proc 9	RCR(inhal): 0.05
Proc 10	RCR(inhal): 0.05

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

Proc 13  
Proc 17

RCR(inhal): 0.05  
RCR(inhal): 0.4980 - Contributing Scenarios 13  
RCR(inhal): 0.05 - Contributing Scenarios 14

## Number of the ES 11

Short title of the exposure scenario

**Metal working fluids / rolling oils**

### List of use descriptors

#### Sector of uses [SU]

SU22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC10: Roller application or brushing

PROC11: Non industrial spraying

PROC13: Treatment of articles by dipping and pouring

PROC17: Lubrication at high energy conditions and in partly open process

#### Environmental release categories [ERC]

ERC8a: Wide dispersive indoor use of processing aids in open systems

#### Product characteristics

Refer to attached safety data sheets

#### Processes and activities covered by the exposure scenario

Covers the use in formulated MWFs (MWFs) including transfer operations, open and contained cutting/machining activities, automated and manual application of corrosion protections, draining and working on contaminated/ reject articles, and disposal of waste oils.

#### Further explanations

Professional use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Assumes a good basic standard of occupational hygiene is implemented

### Contributing Scenarios

Number of the contributing scenario

1\*\*\*

Contributing exposure scenario controlling environmental exposure for  
ERC 8a

#### Further specification

SpERC ESVOC 8.7c.v1 (ESVOC 20),  
assessment tool used: Chesar 2.3.\*\*\*

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

## Amounts used

daily wide dispersive use: 0.014 to/d  
Amounts used (EU): 100000 to/a  
Fraction of Regional tonnage used locally: 0.0005  
Fraction of EU tonnage used in region: 0.1

## Frequency and duration of use

Covers use up to: 365 days\*\*\*

## Environment factors not influenced by risk management

River flow rate: 18000 m<sup>3</sup>/d  
Local freshwater dilution factor: 10  
Local marine water dilution factor: 100

## Other given operational conditions affecting environmental exposure

Indoor/Outdoor use

## Technical conditions and measures at process level (source) to prevent release

Release fraction to air from wide dispersive use (regional only): 15%  
Release fraction to wastewater from wide dispersive use: 5 %  
Release fraction to soil from wide dispersive use (regional only): 5%\*\*\*

## Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m<sup>3</sup>/d): 2000  
The minimum grade of elimination in the sewage plant is (%): 87.5

## Number of the contributing scenario

2\*\*\*

### Contributing exposure scenario controlling worker exposure for PROC 1

#### Further specification

assessment tool used: Chesar 2.3\*\*\*

#### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP  
Covers percentage substance in the product up to 100 % (unless stated differently)

#### Frequency and duration of use

8 h (full shift)

#### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

#### Other given operational conditions affecting workers exposure

Indoor and outdoor use

#### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

3

### Contributing exposure scenario controlling worker exposure for PROC 2

#### Further specification

assessment tool used: Chesar 2.3\*\*\*

#### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP  
Covers percentage substance in the product up to 100 % (unless stated differently)

#### Frequency and duration of use

8 h (full shift)

#### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

#### Other given operational conditions affecting workers exposure

Indoor and outdoor use

#### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

4

### Contributing exposure scenario controlling worker exposure for PROC 3

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

5

## Contributing exposure scenario controlling worker exposure for PROC 5

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

6

## Contributing exposure scenario controlling worker exposure for PROC 8a

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

7

## Contributing exposure scenario controlling worker exposure for PROC 8b

## Further specification

assessment tool used: Chesar 2.3\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

8

## Contributing exposure scenario controlling worker exposure for PROC 10

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

9

## Contributing exposure scenario controlling worker exposure for PROC 11

### Further specification

assessment tool used: StoffenManager

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor use

Room volume > 1000 m<sup>3</sup>

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).\*\*\*

### Technical conditions and measures to control dispersion from source towards the worker

Use in ventilated spray booths only.

### Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested\*\*\*

### Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.

## Number of the contributing scenario

10\*\*\*

## Contributing exposure scenario controlling worker exposure for PROC 11

### Further specification

assessment tool used: StoffenManager

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Frequency and duration of use

Exposure time per day: 6 h/d\*\*\*

## Other given operational conditions affecting workers exposure

Indoor use

Room volume 100 - 1000 m<sup>3</sup>

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Ensure that the task is not carried out by more than one worker simultaneously.\*\*\*

## Technical conditions and measures to control dispersion from source towards the worker

Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 47 % (inhalative).\*\*\*

## Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested\*\*\*

## Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.

## Number of the contributing scenario

11\*\*\*

## Contributing exposure scenario controlling worker exposure for PROC 11

### Further specification

assessment tool used: StoffenManager

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor use

Room volume < 100 m<sup>3</sup>

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Ensure that the task is not carried out by more than one worker simultaneously.\*\*\*

### Technical conditions and measures to control dispersion from source towards the worker

Provide enhanced general ventilation by mechanical means. Effectiveness of LEV (local exhaust ventilation): 47 % (inhalative).\*\*\*

### Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested\*\*\*

### Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly. Wear respiratory protection (Efficiency: 80 %) Alternatively: Use duration max. 5 h.

## Number of the contributing scenario

12

## Contributing exposure scenario controlling worker exposure for PROC 13

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Number of the contributing scenario

13

# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Contributing exposure scenario controlling worker exposure for PROC 17

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use\*\*\*

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear respiratory protection (Efficiency: 90 %) Alternatively: Use duration max. 1 h.\*\*\*

## Number of the contributing scenario

14

## Contributing exposure scenario controlling worker exposure for PROC 17

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP\*\*\*

### Frequency and duration of use

8 h (full shift)\*\*\*

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Operation is carried out at elevated temperature (> 20°C above ambient temperature)

Indoor use

### Technical conditions and measures to control dispersion from source towards the worker

Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 80 % (inhalative).

### Conditions and measures related to personal protection, hygiene and health evaluation

If above technical/organisational control measures are not feasible, then adopt following PPE. If carried out for more than 1h, wear respiratory protection (efficiency 90%).\*\*\*

## Exposure estimation and reference to its source

### Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

Fresh Water (Pelagic)	PEC: 0.004 mg/l; RCR: 0.106
Fresh Water (Sediment)	PEC: 0.033 mg/kg dw; RCR: 0.187
Marine Water (Pelagic)	PEC: 0.0009 mg/l; RCR: 0.1146
Marine Water (Sediment)	PEC: 0.004 mg/kg dw; RCR: 0.204
Agricultural Soil	PEC: 0.0007 mg/kg dw; RCR: 0.052
Sewage Treatment Plant (Effluent)	PEC: 0.0430 mg/l; RCR: 0.0000

### Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 1	EE(inhal): 0.031
Proc 2	EE(inhal): 61.77

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

Proc 3	EE(inhal): 77.21
Proc 5	EE(inhal): 185.3
Proc 8a	EE(inhal): 185.3
Proc 8b	EE(inhal): 92.65
Proc 10	EE(inhal): 185.3
Proc 11	EE(inhal): 0 - Contributing Scenario 9 EE(inhal): 300 - Contributing Scenario 10 EE(inhal): 187.4 - Contributing Scenario 11
Proc 13	EE(inhal): 185.3
Proc 17	EE(inhal): 123.5 - Contributing Scenario 13 EE(inhal): 185.3 - Contributing Scenario 14

## Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 1	RCR(inhal): 0.0001
Proc 2	RCR(inhal): 0.199
Proc 3	RCR(inhal): 0.249
Proc 5	RCR(inhal): 0.598
Proc 8a	RCR(inhal): 0.598
Proc 8b	RCR(inhal): .?
Proc 10	RCR(inhal): 0.598
Proc 11	RCR(inhal): 0 - Contributing Scenarios 9 RCR(inhal): 0.968 - Contributing Scenarios 10 RCR(inhal): 0.605 - Contributing Scenarios 11
Proc 13	RCR(inhal): 0.598
Proc 17	RCR(inhal): 0.399 - Contributing Scenarios 13 RCR(inhal): 0.598 - Contributing Scenarios 14

## Number of the ES 12

Short title of the exposure scenario

**Use in laboratories**

### List of use descriptors

#### Sector of uses [SU]

SU22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Process categories [PROC]

PROC10: Roller application or brushing

PROC15: Use as laboratory reagent

#### Environmental release categories [ERC]

ERC8a: Wide dispersive indoor use of processing aids in open systems

#### Product characteristics

Refer to attached safety data sheets

#### Processes and activities covered by the exposure scenario

Use of small quantities within laboratory settings, including material transfers and equipment cleaning



# SAFETY DATA SHEET



n-Butanol  
10420

Version / Revision 3 .00\*\*\*

## Further explanations

Professional use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Assumes a good basic standard of occupational hygiene is implemented

## Contributing Scenarios

**Number of the contributing scenario** 1  
**Contributing exposure scenario controlling environmental exposure for ERC 8a**

### Further specification

SpERC ESVOC 8.17.v1 (ESVOC 39),  
assessment tool used: Chesar 2.3.\*\*\*

### Amounts used

daily wide dispersive use: 0.000002 to/d

Fraction of Regional tonnage used locally: 0.0005

Fraction of EU tonnage used in region: 0.1

Amounts used (EU): 16 to/a

### Frequency and duration of use

Covers use up to: 365 days\*\*\*

### Environment factors not influenced by risk management

River flow rate: 18000 m<sup>3</sup>/d

Local freshwater dilution factor: 10

Local marine water dilution factor: 100

### Other given operational conditions affecting environmental exposure

Indoor/Outdoor use\*\*\*

### Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 50 %

Release fraction to wastewater from process: 50 %

Release fraction to soil from process: 0%

### Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m<sup>3</sup>/d): 2000

The minimum grade of elimination in the sewage plant is (%): 87.4

**Number of the contributing scenario** 2  
**Contributing exposure scenario controlling worker exposure for PROC 10**

### Further specification

assessment tool used: Chesar 2.3\*\*\*

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)\*\*\*

### Other given operational conditions affecting workers exposure

Indoor and outdoor use\*\*\*

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

**Number of the contributing scenario** 3  
**Contributing exposure scenario controlling worker exposure for PROC 15**

### Further specification

assessment tool used: Chesar 2.3\*\*\*

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)\*\*\*

## Other given operational conditions affecting workers exposure

Indoor and outdoor use\*\*\*

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).\*\*\*

## Exposure estimation and reference to its source

### Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

Fresh Water (Pelagic)	PEC: 0.004 mg/l; RCR: 0.053
Fresh Water (Sediment)	PEC: 0.017 mg/kg dw; RCR: 0.094
Marine Water (Pelagic)	PEC: 0.0005 mg/l; RCR: 0.063
Marine Water (Sediment)	PEC: 0.002 mg/kg dw; RCR: 0.111
Agricultural Soil	PEC: 0.0006 mg/kg dw; RCR: 0.004
Sewage Treatment Plant (Effluent)	PEC: 0.0001 mg/l; RCR: 0.0000

### Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 10	EE(inhal): 185.3
Proc 15	EE(inhal): 30.88

### Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 10	RCR(inhal): 0.598
Proc 15	RCR(inhal): 0.1

## Number of the ES 13

Short title of the exposure scenario

### Polymer processing

## List of use descriptors

### Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

## Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

## Environmental release categories [ERC]

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

## Product characteristics

Refer to attached safety data sheets

## Processes and activities covered by the exposure scenario

Processing of formulated polymers including material transfers, moulding and forming activities, material re-works and associated maintenance\*\*\*

## Further explanations

Industrial use

Human health hazard assessment:

see attached exposure scenario No: 1

Assumes a good basic standard of occupational hygiene is implemented\*\*\*

## Contributing Scenarios

**Number of the contributing scenario**

1

**Contributing exposure scenario controlling environmental exposure for ERC 4**

## Further specification

SpERC ESVOC 4.21a.v1 (ESVOC 44),  
assessment tool used: Chesar 2.3.\*\*\*

## Amounts used

Daily amount per site: 2 to

Annual amount per site: 600 to

## Environment factors not influenced by risk management

River flow rate: 18000 m<sup>3</sup>/d

Local freshwater dilution factor: 10

Local marine water dilution factor: 100

## Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 5 %

Release fraction to wastewater from process: 0 %

Release fraction to soil from process: 0.001%

## Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Onsite treatment off-air. Upgrade Systems in place or implement additional treatment. Assumed Efficiency: 80 % Onsite treatment wastewater. Apply acclimated biological treatment. Assumed Efficiency: 70 %\*\*\*

## Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m<sup>3</sup>/d): 2000

The minimum grade of elimination in the sewage plant is (%): 87.4

## Exposure estimation and reference to its source

### Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

Fresh Water (Pelagic)

PEC: 0.004 mg/l; RCR: 0.053

# SAFETY DATA SHEET



**n-Butanol**  
**10420**

**Version / Revision** 3 .00\*\*\*

---

Fresh Water (Sediment)	PEC: 0.017 mg/kg dw; RCR: 0.094
Marine Water (Pelagic)	PEC: 0.0005 mg/l; RCR: 0.063
Marine Water (Sediment)	PEC: 0.002 mg/kg dw; RCR: 0.111
Agricultural Soil	PEC: 0.003 mg/kg dw; RCR: 0.199
Sewage Treatment Plant (Effluent)	PEC: 0 mg/l; RCR: 0